
# Standard Rectifier

| | | |
|---|---|---|
| $V_{RRM}$ | = | 1800 V |
| $I_{FAV}$ | = | 30 A |
| $V_F$ | = | 1.22 V |


Single Diode

**Part number**

**DMA30E1800HA**




Backside: anode




**Features / Advantages:**

- Planar passivated chips
- Very low leakage current
- Very low forward voltage drop
- Improved thermal behaviour

**Applications:**

- Diode for main rectification
- For single and three phase bridge configurations

**Package:** TO-247

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

**Disclaimer Notice**

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.



© 2019 IXYS all rights reserved

## Rectifier


| Symbol | Definition | Conditions | | Ratings min. | typ. | max. | Unit |
|---|---|---|---|---|---|---|---|
| $V_{RSM}$ | *max. non-repetitive reverse blocking voltage* | | $T_{VJ}$ = 25°C | | | 1900 | V |
| $V_{RRM}$ | *max. repetitive reverse blocking voltage* | | $T_{VJ}$ = 25°C | | | 1800 | V |
| $I_R$ | *reverse current* | $V_R$ = 1800 V | $T_{VJ}$ = 25°C | | | 40 | µA |
| | | $V_R$ = 1800 V | $T_{VJ}$ = 150°C | | | 1.5 | mA |
| $V_F$ | *forward voltage drop* | $I_F$ = 30 A | $T_{VJ}$ = 25°C | | | 1.25 | V |
| | | $I_F$ = 60 A | | | | 1.50 | V |
| | | $I_F$ = 30 A | $T_{VJ}$ = 150°C | | | 1.22 | V |
| | | $I_F$ = 60 A | | | | 1.59 | V |
| $I_{FAV}$ | *average forward current* | $T_C$ = 140°C | $T_{VJ}$ = 175°C | | | 30 | A |
| | | rectangular d = 0.5 | | | | | |
| $V_{F0}$ | *threshold voltage* } *for power loss calculation only* | | $T_{VJ}$ = 175°C | | | 0.83 | V |
| $r_F$ | *slope resistance* } | | | | | 12.8 | mΩ |
| $R_{thJC}$ | *thermal resistance junction to case* | | | | | 0.7 | K/W |
| $R_{thCH}$ | *thermal resistance case to heatsink* | | | | 0.3 | | K/W |
| $P_{tot}$ | *total power dissipation* | | $T_C$ = 25°C | | | 210 | W |
| $I_{FSM}$ | *max. forward surge current* | t = 10 ms; (50 Hz), sine | $T_{VJ}$ = 45°C | | | 370 | A |
| | | t = 8,3 ms; (60 Hz), sine | $V_R$ = 0 V | | | 400 | A |
| | | t = 10 ms; (50 Hz), sine | $T_{VJ}$ = 150°C | | | 315 | A |
| | | t = 8,3 ms; (60 Hz), sine | $V_R$ = 0 V | | | 340 | A |
| $I^2t$ | *value for fusing* | t = 10 ms; (50 Hz), sine | $T_{VJ}$ = 45°C | | | 685 | $A^2s$ |
| | | t = 8,3 ms; (60 Hz), sine | $V_R$ = 0 V | | | 665 | $A^2s$ |
| | | t = 10 ms; (50 Hz), sine | $T_{VJ}$ = 150°C | | | 495 | $A^2s$ |
| | | t = 8,3 ms; (60 Hz), sine | $V_R$ = 0 V | | | 480 | $A^2s$ |
| $C_J$ | *junction capacitance* | $V_R$ = 400 V; f = 1 MHz | $T_{VJ}$ = 25°C | | 10 | | pF |



© 2019 IXYS all rights reserved

| Package TO-247 | | | Ratings | | | |
|---|---|---|---|---|---|---|
| **Symbol** | **Definition** | **Conditions** | **min.** | **typ.** | **max.** | **Unit** |
| $I_{RMS}$ | *RMS current* | per terminal | | | 70 | A |
| $T_{VJ}$ | *virtual junction temperature* | | -55 | | 175 | °C |
| $T_{op}$ | *operation temperature* | | -55 | | 150 | °C |
| $T_{stg}$ | *storage temperature* | | -55 | | 150 | °C |
| **Weight** | | | | 6 | | g |
| $M_D$ | *mounting torque* | | 0.8 | | 1.2 | Nm |
| $F_C$ | *mounting force with clip* | | 20 | | 120 | N |

Product Marking





**Part description**

D = Diode
M = Standard Rectifier
A = (up to 1800V)
30 = Current Rating [A]
E = Single Diode
1800 = Reverse Voltage [V]
HA = TO-247AD (2)

| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|---|---|---|---|---|---|
| Standard | DMA30E1800HA | DMA30E1800HA | Tube | 30 | 455156 |

## Equivalent Circuits for Simulation

** on die level* $T_{VJ} = 175°C$





**Rectifier**

| | | | |
|---|---|---|---|
| $V_{0\,max}$ | *threshold voltage* | 0.83 | V |
| $R_{0\,max}$ | *slope resistance ** | 10.2 | mΩ |




© 2019 IXYS all rights reserved

## Outlines TO-247




| Sym. | Inches | | Millimeter | |
|---|---|---|---|---|
| | min. | max. | min. | max. |
| A | 0.185 | 0.209 | 4.70 | 5.30 |
| A1 | 0.087 | 0.102 | 2.21 | 2.59 |
| A2 | 0.059 | 0.098 | 1.50 | 2.49 |
| D | 0.819 | 0.845 | 20.79 | 21.45 |
| E | 0.610 | 0.640 | 15.48 | 16.24 |
| E2 | 0.170 | 0.216 | 4.31 | 5.48 |
| e | 0.430 BSC | | 10.92 BSC | |
| L | 0.780 | 0.800 | 19.80 | 20.30 |
| L1 | - | 0.177 | - | 4.49 |
| Ø P | 0.140 | 0.144 | 3.55 | 3.65 |
| Q | 0.212 | 0.244 | 5.38 | 6.19 |
| S | 0.242 BSC | | 6.14 BSC | |
| b | 0.039 | 0.055 | 0.99 | 1.40 |
| b2 | 0.065 | 0.094 | 1.65 | 2.39 |
| b4 | 0.102 | 0.135 | 2.59 | 3.43 |
| c | 0.015 | 0.035 | 0.38 | 0.89 |
| D1 | 0.515 | - | 13.07 | - |
| D2 | 0.020 | 0.053 | 0.51 | 1.35 |
| E1 | 0.530 | - | 13.45 | - |
| Ø P1 | - | 0.29 | - | 7.39 |






© 2019 IXYS all rights reserved

## Rectifier





Fig. 1 Forward current versus voltage drop per diode





Fig. 2 Surge overload current





Fig. 3 $I^2t$ versus time per diode





Fig. 4 Power dissipation versus direct output current and ambient temperature





Fig. 5 Max. forward current versus case temperature





Fig. 6 Transient thermal impedance junction to case

Constants for $Z_{thJC}$ calculation:

| i | $R_{thi}$ (K/W) | $t_i$ (s) |
|---|---|---|
| 1 | 0.03 | 0.0003 |
| 2 | 0.072 | 0.0065 |
| 3 | 0.131 | 0.027 |
| 4 | 0.367 | 0.105 |
| 5 | 0.1 | 0.8 |



© 2019 IXYS all rights reserved