NB4N316M

3.3 V AnyLevel™ Receiver to CML Driver/Translator with Input Hysteresis

2.0 GHz Clock / 2.5 Gb/s Data

The NB4N316M is a differential Clock or Data receiver and will accept AnyLevel input signals: LVPECL, CML, LVCMOS, LVTTL, or LVDS. These signals will be translated to CML, operating up to 2.0 GHz or 2.5 Gb/s, respectively. As such, the NB4N316M is ideal for SONET, GigE, Fiber Channel, Backplane and other Clock or Data distribution applications. The CML outputs are 16 mA open collector (see Figure 18) which requires resistor (R_L) load path to V_{TT} termination voltage (see Figure 19). The open collector CML outputs must be terminated to V_{TT} at power up. The differential outputs produce Current–Mode Logic (CML) compatible levels when the receiver is loaded with 50 Ω or 25 Ω loads connected to 1.8 V, 2.5 V or 3.3 V supplies. This simplifies device interface by eliminating a need for coupling capacitors.

The NB4N316M features an input threshold hysteresis of approximately 25 mV, providing increased noise immunity and stability.

The device is offered in a small 8−pin TSSOP package (MSOP−8 compatible). Application notes, models, and support documentation are available at www.onsemi.com.

Features

- Maximum Input Clock Frequency > 2.0 GHz
- Maximum Input Data Rate > 2.5 Gb/s
- Typically 1 ps of RMS Clock Jitter
- Typically 10 ps of Data Dependent Jitter
- 550 ps Typical Propagation Delay
- 150 ps Typical Rise and Fall Times
- Differential CML Outputs
- 25 mV of Receiver Input Threshold Hysteresis
- Operating Range: V_{CC} = 3.0 V to 3.6 V with V_{EE} = 0 V and V_{TT} = 1.8 V to 3.6 V
- Functionally Compatible with Existing 2.5 V / 3.3 V LVEL, LVEP, EP, and SG Devices
- −40°C to +85°C Ambient Operating Temperature
- These are Pb−Free Devices*

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


ON Semiconductor®

www.onsemi.com



TSSOP−8
DT SUFFIX
CASE 948R

MARKING DIAGRAM*



A	= Assembly Location
L	= Wafer Lot
Y	= Year
W	= Work Week
▪	= Pb−Free Package

(Note: Microdot may be in either location)

*For additional marking information, refer to Application Note AND8002/D.




Figure 1. Functional Block Diagram

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 11 of this data sheet.

© Semiconductor Components Industries, LLC, 2016




Figure 2. Pinout (Top View) **and Logic Diagram**

Table 1. Pin Description

Pin	Name	I/O	Description
1	NC	−	No Connect.
2	D	ECL, CML, LVCMOS, LVDS, LVTTL Input	Noninverted Differential Input. (Note 1)
3	$\overline{D}$	ECL, CML, LVCMOS, LVDS, LVTTL Input	Inverted Differential Input. (Note 1)
4	V_{BB}	−	Internally Generated Reference Voltage Supply.
5	V_{EE}	−	Negative Supply Voltage.
6	$\overline{Q}$	CML Output	Inverted Differential Output. Typically Terminated with 50 Ω Resistor to V_{TT}.
7	Q	CML Output	Noninverted Differential Output. Typically Terminated with 50 Ω Resistor to V_{TT}.
8	V_{CC}	−	Positive Supply Voltage.

1. In the differential configuration if no signal is applied on D/$\overline{D}$ input, then the device will be susceptible to self−oscillation.

Table 2. ATTRIBUTES

Characteristics		Value
ESD Protection	Human Body Model Machine Model	> 1000 V > 70 V
Moisture Sensitivity (Note 1)	8−TSSOP	Level 3
Flammability Rating	Oxygen Index: 28 to 34	UL 94 V−0 @ 0.125 in
Transistor Count		225
Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test		

1. For additional information, see Application Note AND8003/D.

Table 3. MAXIMUM RATINGS

Symbol	Parameter	Condition 1	Condition 2	Rating	Unit
V_{CC}	Positive Power Supply	V_{EE} = −0.5 V		4	V
V_{EE}	Negative Power Supply	V_{CC} = +0.5 V		−4	V
V_I	Positive Input Negative Input	V_{EE} = 0 V V_{CC} = 0 V	V_I = V_{CC} +0.4 V V_I = V_{EE} –0.4 V	4 −4	V V
V_O	Output Voltage Minimum Maximum			V_{EE} + 600 V_{CC} + 400	mV mV
T_A	Operating Temperature Range			−40 to +85	°C
T_{stg}	Storage Temperature Range			−65 to +150	°C
θ_{JA}	Thermal Resistance (Junction−to−Ambient) (Note 2)	0 lfpm 500 lfpm	TSSOP−8 TSSOP−8	190 130	°C/W °C/W
θ_{JC}	Thermal Resistance (Junction−to−Case)	1S2P (Note 2)	TSSOP−8	41 to 44	°C/W
T_{sol}	Wave Solder	< 3 Sec @ 260°C		265	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

2. JEDEC standard multilayer board − 1S2P (1 signal, 2 power) with 8 filled thermal vias under exposed pad.

Table 4. DC CHARACTERISTICS, CLOCK Inputs, CML Outputs V_{CC} = 3.0 V to 3.6 V, V_{EE} = 0 V, T_A = −40°C to +85°C

Symbol	Characteristic	Min	Typ	Max	Unit
I_{CC}	Power Supply Current (Inputs and Outputs Open)		20	30	mA
R_L = 50 Ω, V_{TT} = 3.6 V to 2.5 V					
V_{OH}	Output HIGH Voltage (Note 3)	V_{TT} − 60	V_{TT} − 10	V_{TT}	mV
V_{OL}	Output LOW Voltage (Note 3)	V_{TT} − 1100	V_{TT} − 800	V_{TT} − 640	mV
$\|V_{OD}\|$	Differential Output Voltage Magnitude	640	780	1000	mV
R_L = 25 Ω, V_{TT} = 3.6 V to 2.5 V ±5%					
V_{OH}	Output HIGH Voltage (Note 3)	V_{TT} − 60	V_{TT} − 10	V_{TT}	mV
V_{OL}	Output LOW Voltage (Note 3)	V_{TT} − 550	V_{TT} − 400	V_{TT} − 320	mV
$\|V_{OD}\|$	Differential Output Voltage Magnitude	320	390	500	mV
R_L = 50 Ω, V_{TT} = 1.8 V ±5%					
V_{OH}	Output HIGH Voltage (Note 3)	V_{TT} − 170	V_{TT} − 10	V_{TT}	mV
V_{OL}	Output LOW Voltage (Note 3)	V_{TT} − 1100	V_{TT} − 800	V_{TT} − 640	mV
$\|V_{OD}\|$	Differential Output Voltage Magnitude	570	780	1000	mV
R_L = 25 Ω, V_{TT} = 1.8 V ±5%					
V_{OH}	Output HIGH Voltage (Note 3)	V_{TT} − 85	V_{TT} − 10	V_{TT}	mV
V_{OL}	Output LOW Voltage (Note 3)	V_{TT} − 500	V_{TT} − 400	V_{TT} − 320	mV
$\|V_{OD}\|$	Differential Output Voltage Magnitude	285	390	500	mV
DIFFERENTIAL INPUT DRIVEN SINGLE−ENDED (Figures 14 and 16)					
V_{th}	Input Threshold Reference Voltage Range (Note 5)	V_{EE}		V_{CC}	mV
V_{IH}	Single−ended Input HIGH Voltage	V_{th} + 100		V_{CC} + 400	mV
V_{IL}	Single−ended Input LOW Voltage	V_{EE} − 400		V_{th} − 100	mV
V_{BB}	Internally Generated Reference Voltage Supply (Loaded with −100 μA)	V_{CC} − 1500	V_{CC} − 1400	V_{CC} − 1300	mV
DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY (Figures 15 and 17)					
V_{IHD}	Differential Input HIGH Voltage	V_{EE}		V_{CC} + 400	mV
V_{ILD}	Differential Input LOW Voltage	V_{EE} − 400		V_{CC} − 100	mV
V_{CMR}	Input Common Mode Range (Differential Configuration)	V_{EE}		V_{CC}	mV
$V_{ID(HYST)}$	Differential Input Voltage Hysteresis (V_{IHD} − V_{ILD})		25		mV
$\|V_{ID}\|$	Differential Input Voltage Magnitude ($\|V_{IHD} - V_{ILD}\|$) (Note 7)	100		V_{CC} − V_{EE}	mV
C_{IN}	Input Capacitance (Note 7)		1.5		pF

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm.


3. CML outputs require R_L receiver termination resistors to V_{TT} for proper operation. Outputs must be connected through R_L to V_{TT} at power up. The output parameters vary 1:1 with V_{TT}. V_{TT} = 1.71 V to 3.6 V.
4. Input parameters vary 1:1 with V_{CC}.
5. V_{th} is applied to the complementary input when operating in single−ended mode.
6. V_{CMR} (MIN) varies 1:1 with V_{EE}, V_{CMR} max varies 1:1 with V_{CC}.
7. Parameter guaranteed by design and evaluation but not tested in production.

Table 5. AC CHARACTERISTICS V_{CC} = 3.0 V to 3.6 V, V_{EE} = 0 V; (Note 8)

Symbol	Characteristic	−40°C			25°C			85°C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
V_{OUTPP}	Output Voltage Amplitude (R_L = 50 Ω) $f_{in} \le 1$ GHz (See Figure 12) $f_{in} \le 1.5$ GHz $f_{in} \le 2.0$ GHz	 550 400 200	 660 640 400		 550 400 200	 660 640 400		 550 400 200	 660 640 400		mV
V_{OUTPP}	Output Voltage Amplitude (R_L = 25 Ω) $f_{in} \le 1$ GHz (See Figure 12) $f_{in} \le 1.5$ GHz $f_{in} \le 2.0$ GHz	 280 280 200	 370 360 300		 280 280 200	 370 360 400		 280 280 200	 370 360 400		mV
f_{DATA}	Maximum Operating Data Rate	1.5	2.5		1.5	2.5		1.5	2.5		Gb/s
t_{PLH}, t_{PHL}	Propagation Delay to Output Differential @ 0.25 GHz	350	550	750	350	550	750	350	550	750	ps
t_{SKEW}	Duty Cycle Skew (Note 9) Device to Device Skew (Note 13)		2 20	20 100		2 20	20 100		2 20	20 100	ps
t_{JITTER}	RMS Random Clock Jitter R_L = 50 Ω and R_L = 25 Ω (Note 11) f_{in} = 750 MHz f_{in} = 1.5 GHz f_{in} = 2.0 GHz Peak−to−Peak Data Dependent Jitter R_L = 50 Ω f_{DATA} = 1.5 Gb/s (Note 12) f_{DATA} = 2.5 Gb/s Peak−to−Peak Data Dependent Jitter R_L = 25 Ω f_{DATA} = 1.5 Gb/s (Note 12) f_{DATA} = 2.5 Gb/s		 1 1 1 15 20 5 10	 3 3 3 55 85 35 35		 1 1 1 15 20 5 10	 3 3 3 55 85 35 35		 1 1 1 15 20 5 10	 3 3 3 55 85 35 35	ps
V_{INPP}	Input Voltage Swing/Sensitivity (Differential Configuration) (Note 10)	200			200			200			mV
t_r t_f	Output Rise/Fall Times @ 0.25 GHz (20% − 80%) Q, $\overline{Q}$		150	300		150	300		150	300	ps

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm.

8. Measured by forcing V_{INPP} (MIN) from a 50% duty cycle clock source. All output loaded with an external R_L = 50 Ω and R_L = 25 Ω to V_{TT}. Outputs must be connected through R_L to V_{TT} at power up. Input edge rates 150 ps (20% − 80%).
9. Duty cycle skew is measured between differential outputs using the deviations of the sum of T_{pw-} and T_{pw+} @ 0.25 GHz.
10. V_{INPP} (MAX) cannot exceed V_{CC} − V_{EE}. Input voltage swing is a single−ended measurement operating in differential mode.
11. Additive RMS jitter with 50% duty cycle clock signal.
12. Additive peak−to−peak data dependent jitter with input NRZ data signal (PRBS 2^{23}–1).
13. Device to device skew is measured between outputs under identical transition @ 0.5 GHz.



(V_{CC} − V_{EE} = 3.3 V V_{TT} = 3.3 V @ 25°C V_{in} = 100 mV) **(V_{CC} − V_{EE} = 3.0 V V_{TT} = 1.71 V @25°C V_{in} = 100 mV)**

Figure 3. Output Voltage Amplitude (V_{OUTPP}) versus Input Clock Frequency (f_{IN}) at Ambient Temperature (Typical)

NB4N316M




Figure 4. Data Dependent Jitter vs. Frequency and Temperature (V_{CC} − V_{EE} = 3.3 V; V_{TT} = 3.3 V @ 25°C; V_{IN} = 100 mV; PRBS 2^{23}–1; R_L = 50 Ω)




Figure 5. Data Dependent Jitter vs. Frequency and Temperature (V_{CC} − V_{EE} = 3.3 V; V_{TT} = 3.3 V @ 25°C; V_{IN} = 100 mV; PRBS 2^{23}–1; R_L = 25 Ω)




Figure 6. Typical Propagation Delay vs. Temperature (V_{CC} − V_{EE} = 3.3 V; V_{TT} = 3.3 V @ 25°C; V_{in} = 100 mV; R_L = 50 Ω)




Figure 7. Typical Propagation Delay vs. Input Offset Voltage (V_{CC} − V_{EE} = 3.3 V; V_{TT} = 3.3 V @ 25°C; V_{in} = 100 mV R_L = 50 Ω)




Figure 8. Supply Current vs. Temperature




Figure 9. Typical Differential Output Waveform at 750 Mb/s
(R_L = 50 Ω Left Plot, R_L = 25 Ω Right Plot, V_{in} = 100 mV, System DDJ = 24 ps)




Figure 10. Typical Differential Output Waveform 1.5 Gb/s
(R_L = 50 Ω Left Plot, R_L = 25 Ω Right Plot, V_{in} = 100 mV, System DDJ = 25 ps)




Figure 11. Typical Differential Output Waveform 2.5 Gb/s
(R_L = 50 Ω Left Plot, R_L = 25 Ω Right Plot, V_{in} = 100 mV, System DDJ = 24 ps)




Figure 12. AC Reference Measurement




Figure 13. Typical Termination for Output Driver and Device Evaluation (See Application Note AND8020/D − Termination of ECL Logic Devices.)




Figure 14. Differential Input Driven Single−Ended




Figure 15. Differential Inputs Driven Differentially




Figure 16. V_{th} Diagram




Figure 17. V_{CMR} Diagram




Figure 18. CML Input and Output Structure




Figure 19. Typical Examples of the Application Interface

ORDERING INFORMATION

Device	Package	Shipping†
NB4N316MDTG	TSSOP−8 (Pb−Free)	100 Units / Rail
NB4N316MDTR2G	TSSOP−8 (Pb−Free)	2500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Resource Reference of Application Notes

AN1405/D − ECL Clock Distribution Techniques

AN1406/D − Designing with PECL (ECL at +5.0 V)

AN1503/D − ECLinPS™ I/O SPiCE Modeling Kit

AN1504/D − Metastability and the ECLinPS Family

AN1568/D − Interfacing Between LVDS and ECL

AN1672/D − The ECL Translator Guide

AND8001/D − Odd Number Counters Design

AND8002/D − Marking and Date Codes


AND8020/D − Termination of ECL Logic Devices

AND8066/D − Interfacing with ECLinPS

AND8090/D − AC Characteristics of ECL Devices

PACKAGE DIMENSIONS

TSSOP−8
DT SUFFIX
CASE 948R−02
ISSUE A



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
6. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE −W−.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	2.90	3.10	0.114	0.122
B	2.90	3.10	0.114	0.122
C	0.80	1.10	0.031	0.043
D	0.05	0.15	0.002	0.006
F	0.40	0.70	0.016	0.028
G	0.65 BSC		0.026 BSC	
K	0.25	0.40	0.010	0.016
L	4.90 BSC		0.193 BSC	
M	0 °	6 °	0 °	6 °

AnyLevel and ECLinPS are trademarks of Semiconductor Components INdustries, LLC (SCILLC).

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative