


SHOWN FROM COMPONENT SIDE

REVISIONS			
	DESCRIPTION	APPR	DATE
REV A	PROTOTYPE RELEASE		


SIZE	QTY	SYM	PLTD
0.125	4	+	PLTD
0.035	17	×	PLTD
0.094	6	□	PLTD
0.19	6	◇	PLTD
0.07	3	⊗	NPLTD
0.015	240	⊗	PLTD

#### NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 4 OZ. COPPER CLAD  
THICKNESS .062 +/- .006 TOTAL OF 6 LAYERS.
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE  
ELECTRODEPOSITED TIN-LEAD COMPOSITION  
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC).
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT.
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
5. UNUSED SMD COMPONENTS SHOULD BE FREE OF SOLDER.
6. FILL UP ALL VIAS WITH SOLDER.
7. SCORING:



8. PLEASE LOOK AT THE README FILE FOR THE OTHER REQUIREMENTS.

APPROVALS			 <b>LINEAR TECHNOLOGY</b> 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
	INIT	DATE		
DRAWN			<b>TITLE: FABRICATION DRAWING</b> <b>2-PHASE DUAL OUTPUT POWER SUPPLY</b>	
CHECK				
DESIGN	KIM T.	08-02-02		
ENGR	WEI C.	08-02-02	<b>SIZE A DEMO</b> <b>DC447A-1 * LTC3728EUH</b>	
SCALE = NONE			DES- 0000	REV. A
			SHT 1 of 1	