
# IXYS

## Q3-Class HiperFET™ Power MOSFET


# IXFN32N100Q3

$V_{DSS}$ = 1000V
$I_{D25}$ = 28A
$R_{DS(on)}$ ≤ 320mΩ
$t_{rr}$ ≤ 300ns

N-Channel Enhancement Mode
Fast Intrinsic Rectifier




**miniBLOC**
E153432




G = Gate D = Drain
S = Source

Either Source Terminal S can be used as the Source Terminal or the Kelvin Source (Gate Return) Terminal.

| Symbol | Test Conditions | Maximum Ratings | |
|---|---|---|---|
| $V_{DSS}$ | $T_J$ = 25°C to 150°C | 1000 | V |
| $V_{DGR}$ | $T_J$ = 25°C to 150°C, $R_{GS}$ = 1MΩ | 1000 | V |
| $V_{GSS}$ | Continuous | ±30 | V |
| $V_{GSM}$ | Transient | ±40 | V |
| $I_{D25}$ | $T_C$ = 25°C | 28 | A |
| $I_{DM}$ | $T_C$ = 25°C, Pulse Width Limited by $T_{JM}$ | 96 | A |
| $I_A$ | $T_C$ = 25°C | 32 | A |
| $E_{AS}$ | $T_C$ = 25°C | 2 | J |
| dv/dt | $I_S \le I_{DM}$, $V_{DD} \le V_{DSS}$, $T_J \le 150°C$ | 50 | V/ns |
| $P_D$ | $T_C$ = 25°C | 780 | W |
| $T_J$ | | -55 ... +150 | °C |
| $T_{JM}$ | | 150 | °C |
| $T_{stg}$ | | -55 ... +150 | °C |
| $V_{ISOL}$ | 50/60 Hz, RMS, t = 1minute | 2500 | V~ |
| | $I_{ISOL} \le$ 1mA, t = 1s | 3000 | V~ |
| $M_d$ | Mounting Torque for Base Plate | 1.5/13 | Nm/lb.in. |
| | Terminal Connection Torque | 1.3/11.5 | Nm/lb.in. |
| Weight | | 30 | g |

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $BV_{DSS}$ | $V_{GS}$ = 0V, $I_D$ = 3mA | 1000 | | | V |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D$ = 8mA | 3.5 | | 6.5 | V |
| $I_{GSS}$ | $V_{GS}$ = ±30V, $V_{DS}$ = 0V | | | ±200 | nA |
| $I_{DSS}$ | $V_{DS} = V_{DSS}$, $V_{GS}$ = 0V | | | 50 | μA |
| | $T_J$ = 125°C | | | 2 | mA |
| $R_{DS(on)}$ | $V_{GS}$ = 10V, $I_D$ = 16A, Note 1 | | | 320 | mΩ |

### Features

- International Standard Package
- Low Intrinsic Gate Resistance
- miniBLOC with Aluminum Nitride Isolation
- Low Package Inductance
- Fast Intrinsic Rectifier
- Low $R_{DS(on)}$ and $Q_G$

### Advantages

- High Power Density
- Easy to Mount
- Space Savings

### Applications

- DC-DC Converters
- Battery Chargers
- Switch-Mode and Resonant-Mode Power Supplies
- DC Choppers
- Temperature and Lighting Controls

© 2020 IXYS CORPORATION, All Rights Reserved

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $g_{fs}$ | $V_{DS}$ = 20V, $I_D$ = 16A, Note 1 | 20 | 32 | | S |
| $C_{iss}$ | $V_{GS}$ = 0V, $V_{DS}$ = 25V, f = 1MHz | | 10.9 | | nF |
| $C_{oss}$ | | | 745 | | pF |
| $C_{rss}$ | | | 67 | | pF |
| $R_{Gi}$ | Gate Input Resistance | | 0.20 | | Ω |
| $t_{d(on)}$ | **Resistive Switching Times** | | 45 | | ns |
| $t_r$ | $V_{GS}$ = 10V, $V_{DS}$ = 0.5 • $V_{DSS}$, $I_D$ = 16A | | 15 | | ns |
| $t_{d(off)}$ | $R_G$ = 1Ω (External) | | 54 | | ns |
| $t_f$ | | | 12 | | ns |
| $Q_{g(on)}$ | $V_{GS}$ = 10V, $V_{DS}$ = 0.5 • $V_{DSS}$, $I_D$ = 16A | | 195 | | nC |
| $Q_{gs}$ | | | 60 | | nC |
| $Q_{gd}$ | | | 78 | | nC |
| $R_{thJC}$ | | | | 0.16 | °C/W |
| $R_{thCS}$ | | | 0.05 | | °C/W |

**Source-Drain Diode**

| Symbol | Test Conditions ($T_J$ = 25°C Unless Otherwise Specified) | Characteristic Values Min. | Typ. | Max. | |
|---|---|---|---|---|---|
| $I_S$ | $V_{GS}$ = 0V | | | 32 | A |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$ | | | 128 | A |
| $V_{SD}$ | $I_F$ = $I_S$, $V_{GS}$ = 0V, Note 1 | | | 1.4 | V |
| $t_{rr}$ | $I_F$ = 16A, -di/dt = 100A/μs | | | 300 | ns |
| $Q_{RM}$ | $V_R$ = 100V, $V_{GS}$ = 0V | | 1.2 | | μC |
| $I_{RM}$ | | | 12.3 | | A |

Note 1. Pulse test, t ≤ 300μs, duty cycle, d ≤ 2%.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,860,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123 B1 6,306,728 B1 6,404,065 B1 6,534,343 6,583,505 6,683,344 6,710,405 B2 6,710,463 6,727,585 6,759,692 6,771,478 B2 7,005,734 B2 7,063,975 B2 7,071,537 7,157,338B2

**Fig. 1. Output Characteristics @ $T_J$ = 25°C**





**Fig. 2. Extended Output Characteristics @ $T_J$ = 25°C**





**Fig. 3. Output Characteristics @ $T_J$ = 125°C**





**Fig. 4. $R_{DS(on)}$ Normalized to $I_D$ = 16A Value vs. Junction Temperature**





**Fig. 5. $R_{DS(on)}$ Normalized to $I_D$ = 16A Value vs. Drain Current**






**Fig. 6. Maximum Drain Current vs. Case Temperature**




© 2020 IXYS CORPORATION, All Rights Reserved

**Fig. 7. Input Admittance**





**Fig. 8. Transconductance**





**Fig. 9. Forward Voltage Drop of Intrinsic Diode**





**Fig. 10. Gate Charge**





**Fig. 11. Capacitance**







**Fig. 12. Forward-Bias Safe Operating Area**





IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

**Fig. 13. Maximum Transient Thermal Impedance**




© 2020 IXYS CORPORATION, All Rights Reserved

**SOT-227 Outline**




| SYM | INCHES | | MILLIMETERS | |
|---|---|---|---|---|
| | MIN | MAX | MIN | MAX |
| A | 1.224 | 1.260 | 31.10 | 32.00 |
| B | .303 | .327 | 7.70 | 8.30 |
| C | .161 | .173 | 4.10 | 4.40 |
| D | .161 | .173 | 4.10 | 4.40 |
| E | .161 | .173 | 4.10 | 4.40 |
| F | .587 | .598 | 14.90 | 15.20 |
| G | 1.181 | 1.201 | 30.00 | 30.50 |
| H | 1.488 | 1.508 | 37.80 | 38.30 |
| J | .461 | .484 | 11.70 | 12.30 |
| L | .030 | .033 | 0.75 | 0.85 |
| M | .492 | .512 | 12.50 | 13.00 |
| N | .984 | 1.004 | 25.00 | 25.50 |
| O | .075 | .087 | 1.90 | 2.20 |
| S | .181 | .193 | 4.60 | 4.90 |
| U | .000 | .005 | 0.00 | 0.13 |

1. NUT MATERIAL:
   STANDARD – Low carbon steel with Ni plating.
   OPTIONAL: – Brass Nut is available.
   PART NUMBER–BN
2. ALL METAL SURFACE ARE PRE NI PLATED EXCEPT TRIM AREA.




Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

© 2020 IXYS CORPORATION, All Rights Reserved