


SHOWN FROM COMPONENT SIDE


REVISIONS			
REV	DESCRIPTION	APPR	DATE
B-2	FINAL FABRICATION	MT	07-26-06

SIZE	QTY	SYM	PLATED	TOL
0.19	4	+	YES	+/-0.003"
0.064	7	×	YES	+/-0.003"
0.035	66	□	YES	+/-0.003"
0.012	307	◇	YES	+/-0.003"
0.07	2	⊗	NO	+/-0.003"
0.1	2	⊗	YES	+/-0.003"
0.04	44	+ ^A	YES	+/-0.003"

NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
FINISHED THICKNESS TO BE 0.062" +/- .005"
TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE
OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
- DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, 0.001" THICK MIN.
ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/-0.003"
IN RELATION TO CENTER
- FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.
WHITE TIN IMMERSION (OMIKRON).
FOR SILKSCREEN: USE WHITE NON-CONDUCTIVE INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
- SCORING FOR PANELIZED PCB:



APPROVALS			 <div> 1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 LTC CONFIDENTIAL- FOR CUSTOMER USE ONLY </div>	
	INIT	DATE		
DRAWN			TITLE: FABRICATION DRAWING USB SERIAL CONTROLLER II	
CHECK				
DESIGN	KIM T.	07-26-06	SIZE A DEMO DC590B-2 REV. B-2	
ENGR	MARK T.	07-26-06		
SCALE = NONE			SHT 1 of 1	