


**POWER MOS V®**

Power MOS V® is a new generation of high voltage N-Channel enhancement mode power MOSFETs. This new technology minimizes the JFET effect, increases packing density and reduces the on-resistance. Power MOS V® also achieves faster switching speeds through optimized gate layout.



- **Faster Switching**
- **100% Avalanche Tested**
- **Lower Leakage**
- **Popular SOT-227 Package**



| Symbol         | Parameter                                                      | APT8015JVR | UNIT  |
|----------------|----------------------------------------------------------------|------------|-------|
| $V_{DSS}$      | Drain-Source Voltage                                           | 800        | Volts |
| $I_D$          | Continuous Drain Current @ $T_C = 25^\circ\text{C}$            | 44         | Amps  |
| $I_{DM}$       | Pulsed Drain Current <sup>①</sup>                              | 176        |       |
| $V_{GS}$       | Gate-Source Voltage Continuous                                 | $\pm 30$   | Volts |
| $V_{GSM}$      | Gate-Source Voltage Transient                                  | $\pm 40$   |       |
| $P_D$          | Total Power Dissipation @ $T_C = 25^\circ\text{C}$             | 700        | Watts |
|                | Linear Derating Factor                                         | 5.6        | W/°C  |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range               | -55 to 150 | °C    |
| $T_L$          | Lead Temperature: 0.063" from Case for 10 Sec.                 | 300        |       |
| $I_{AR}$       | Avalanche Current <sup>①</sup> (Repetitive and Non-Repetitive) | 44         | Amps  |
| $E_{AR}$       | Repetitive Avalanche Energy <sup>①</sup>                       | 50         | mJ    |
| $E_{AS}$       | Single Pulse Avalanche Energy <sup>④</sup>                     | 3600       |       |

**STATIC ELECTRICAL CHARACTERISTICS**

| Symbol       | Characteristic / Test Conditions                                                                   | MIN | TYP | MAX       | UNIT    |
|--------------|----------------------------------------------------------------------------------------------------|-----|-----|-----------|---------|
| $BV_{DSS}$   | Drain-Source Breakdown Voltage ( $V_{GS} = 0V, I_D = 250\mu A$ )                                   | 800 |     |           | Volts   |
| $I_{D(on)}$  | On State Drain Current <sup>②</sup> ( $V_{DS} > I_{D(on)} \times R_{DS(on)}$ Max, $V_{GS} = 10V$ ) | 44  |     |           | Amps    |
| $R_{DS(on)}$ | Drain-Source On-State Resistance <sup>②</sup> ( $V_{GS} = 10V, 0.5 I_{D(Cont.)}$ )                 |     |     | 0.150     | Ohms    |
| $I_{DSS}$    | Zero Gate Voltage Drain Current ( $V_{DS} = V_{DSS}, V_{GS} = 0V$ )                                |     |     | 100       | $\mu A$ |
|              | Zero Gate Voltage Drain Current ( $V_{DS} = 0.8 V_{DSS}, V_{GS} = 0V, T_C = 125^\circ\text{C}$ )   |     |     | 500       |         |
| $I_{GSS}$    | Gate-Source Leakage Current ( $V_{GS} = \pm 30V, V_{DS} = 0V$ )                                    |     |     | $\pm 100$ | nA      |
| $V_{GS(th)}$ | Gate Threshold Voltage ( $V_{DS} = V_{GS}, I_D = 5mA$ )                                            | 2   |     | 4         | Volts   |

 **CAUTION:** These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

**USA**

405 S.W. Columbia Street

**EUROPE**

Avenue J.F. Kennedy Bât B4 Parc Cadéra Nord

**APT Website - <http://www.advancedpower.com>**

Bend, Oregon 97702-1035

F-33700 Merignac - France

Phone: (541) 382-8028

Phone: (33) 5 57 92 15 15

FAX: (541) 388-0364

FAX: (33) 5 56 47 97 61

# DYNAMIC CHARACTERISTICS

APT8015JVR

| Symbol       | Characteristic               | Test Conditions                                                                                    | MIN | TYP   | MAX   | UNIT |
|--------------|------------------------------|----------------------------------------------------------------------------------------------------|-----|-------|-------|------|
| $C_{iss}$    | Input Capacitance            | $V_{GS} = 0V$<br>$V_{DS} = 25V$<br>$f = 1 \text{ MHz}$                                             |     | 14715 | 17650 | pF   |
| $C_{oss}$    | Output Capacitance           |                                                                                                    |     | 1470  | 2050  |      |
| $C_{rss}$    | Reverse Transfer Capacitance |                                                                                                    |     | 794   | 1190  |      |
| $Q_g$        | Total Gate Charge ③          | $V_{GS} = 10V$<br>$V_{DD} = 0.5 V_{DSS}$<br>$I_D = I_{D[Cont.]} @ 25^\circ C$                      |     | 690   | 1035  | nC   |
| $Q_{gs}$     | Gate-Source Charge           |                                                                                                    |     | 75    | 110   |      |
| $Q_{gd}$     | Gate-Drain ("Miller") Charge |                                                                                                    |     | 275   | 410   |      |
| $t_{d(on)}$  | Turn-on Delay Time           | $V_{GS} = 15V$<br>$V_{DD} = 0.5 V_{DSS}$<br>$I_D = I_{D[Cont.]} @ 25^\circ C$<br>$R_G = 0.6\Omega$ |     | 22    | 44    | ns   |
| $t_r$        | Rise Time                    |                                                                                                    |     | 20    | 40    |      |
| $t_{d(off)}$ | Turn-off Delay Time          |                                                                                                    |     | 97    | 145   |      |
| $t_f$        | Fall Time                    |                                                                                                    |     | 15    | 30    |      |

# SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

| Symbol   | Characteristic / Test Conditions                                           | MIN | TYP  | MAX | UNIT    |
|----------|----------------------------------------------------------------------------|-----|------|-----|---------|
| $I_S$    | Continuous Source Current (Body Diode)                                     |     |      | 44  | Amps    |
| $I_{SM}$ | Pulsed Source Current ① (Body Diode)                                       |     |      | 176 |         |
| $V_{SD}$ | Diode Forward Voltage ② ( $V_{GS} = 0V$ , $I_S = -I_{D[Cont.]}$ )          |     |      | 1.3 | Volts   |
| $t_{rr}$ | Reverse Recovery Time ( $I_S = -I_{D[Cont.]}$ , $di_S/dt = 100A/\mu s$ )   |     | 1000 |     | ns      |
| $Q_{rr}$ | Reverse Recovery Charge ( $I_S = -I_{D[Cont.]}$ , $di_S/dt = 100A/\mu s$ ) |     | 34   |     | $\mu C$ |

# THERMAL/PACKAGE CHARACTERISTICS

| Symbol          | Characteristic                                                                        | MIN  | TYP | MAX  | UNIT         |
|-----------------|---------------------------------------------------------------------------------------|------|-----|------|--------------|
| $R_{\theta JC}$ | Junction to Case                                                                      |      |     | 0.18 | $^\circ C/W$ |
| $R_{\theta JA}$ | Junction to Ambient                                                                   |      |     | 40   |              |
| $V_{isolation}$ | RMS Voltage (50-60 Hz Sinusoidal Waveform From Terminals to Mounting Base for 1 Min.) | 2500 |     |      | Volts        |
| Torque          | Maximum Torque for Device Mounting Screws and Electrical Terminations.                |      |     | 13   | lb•in        |

① Repetitive Rating: Pulse width limited by maximum junction temperature.

③ See MIL-STD-750 Method 3471

② Pulse Test: Pulse width < 380  $\mu s$ , Duty Cycle < 2%

④ Starting  $T_j = +25^\circ C$ ,  $L = 3.72mH$ ,  $R_G = 25\Omega$ , Peak  $I_L = 44A$

APT Reserves the right to change, without notice, the specifications and information contained herein.




FIGURE 1, MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION

# APT8015JVR




FIGURE 2, TYPICAL OUTPUT CHARACTERISTICS




FIGURE 3, TYPICAL OUTPUT CHARACTERISTICS




FIGURE 4, TYPICAL TRANSFER CHARACTERISTICS




FIGURE 5,  $R_{DS(ON)}$  vs DRAIN CURRENT




FIGURE 6, MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 7, BREAKDOWN VOLTAGE vs TEMPERATURE




FIGURE 8, ON-RESISTANCE vs. TEMPERATURE




FIGURE 9, THRESHOLD VOLTAGE vs TEMPERATURE




FIGURE 10, MAXIMUM SAFE OPERATING AREA




FIGURE 11, TYPICAL CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE




FIGURE 12, GATE CHARGES vs GATE-TO-SOURCE VOLTAGE





FIGURE 13, TYPICAL SOURCE-DRAIN DIODE FORWARD VOLTAGE

### SOT-227 (ISOTOP®) Package Outline



Dimensions in Millimeters and (Inches)