


SIZE	QTY	SYM	PLATED	TOL
70	2	+	NO	+/-0.0
10	88	X	YES	+/-0.0
95	7	□	YES	+/-0.0
35	3	◇	YES	+/-0.0

NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600. PCBs ARE TO BE ROHS COMPLIANT.
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISH ON OUTER LAYERS.
1 OZ. COPPER FINISH ON INNER LAYERS.
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS.
FLAMMABILITY RATING: 94 V-0 MINIMUM .
- SIZE: DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
- DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/--.003 INCH IN RELATION TO CENTER
- FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
GOLD IMMERSION BOTH SIDES.(LEAD FREE SOLDER FOR PROTOTYPE)
- SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
BUT YOU MAY MODIFY PAD SIZE TO MEET END FINISH.
- SCORING: (FOR PRODUCTION RUN ONLY)



FAB DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ± 1
2 PLACE ±.01 3 PLACE ±.005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS

INIT	DATE
PCB DESIGNER J. WU	10/15/07
ENGINEER W. Gu	10/15/07
CHECK	



TITLE: LT3757EDD
High Efficiency SEPIC Converter

SIZE	DEMO	REV.
A	DC1341A	A

SCALE = NONE

SHT 1 of 1