

Broadband, Fully-Differential, 14-/16-Bit ADC Driver Amplifier

Check for Samples: [THS770012](#)

FEATURES

- **900MHz Bandwidth at Gain of +10dB**
- **3300V/ μ s Slew Rate, $V_{OUT} = 2V$ step**
- **Adjustable Gain: +10dB to +13.7dB**
- **IMD₃: –100dBc, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$, $f = 100MHz$**
- **OIP3: 47dBm, $f = 100MHz$**
- **Noise Figure: 10.7 dB, $f = 100MHz$**

APPLICATIONS

- **14-/16-Bit ADC Driver**
- **ADC Driver for Wireless Base Station Signal Chains: GSM, WCDMA, MC-GSM, LTE**
- **ADC Driver for High Dynamic Range Test and Measurement Equipment**

Figure 1. THS770012 Driving 16-Bit ADC





Figure 2. FFT Plot with Two-Tone Input at 96MHz and 100MHz (see [Application Information](#) section)



DESCRIPTION

The THS770012 is a wideband, fully-differential amplifier, with adjustable gain range from +10dB to +13.7dB (with external components). It is designed and optimized specifically for driving 16-bit analog-to-digital converters (ADCs) at input frequencies up to 130MHz, and 14-bit ADCs at input frequencies up to 200MHz. This device provides high bandwidth, high-voltage output with low distortion and low noise, critical in high-speed data acquisition systems that require very high dynamic range, such as wireless base stations and test and measurement applications. This device also makes an excellent differential amplifier for general-purpose, high-speed differential signal chain and short line driver applications.

The THS770012 operates on a nominal +5V single supply, offers very fast, 7.5ns maximum recovery time from overdrive conditions, and has a power-down mode for power saving. The THS770012 is offered in a Pb-free (RoHS compliant) and green, QFN-24 thermally-enhanced package. It is characterized for operation over the industrial temperature range of –40°C to +85°C.

RELATED DEVICES

DEVICE	DESCRIPTION
THS770006	Fixed Gain of +6dB, wideband, low-noise, low-distortion, fully-differential amplifier
THS4509	Wideband, low-noise, low-distortion, fully-differential amplifier
PGA870	Wideband, low-noise, low-distortion, fully-differential, digitally-programmable gain amplifier
ADS5481 to ADS5485	16-bit, 80MSPS to 200MSPS ADCs
ADS6145	14-bit, 125MSPS ADC
ADS6149	14-bit, 250MSPS ADC



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PowerPAD is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2010–2012, Texas Instruments Incorporated



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.


ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

PACKAGE/ORDERING INFORMATION⁽¹⁾

PRODUCT	PACKAGE TYPE	PACKAGE DESIGNATOR	SPECIFIED TEMPERATURE RANGE	PACKAGE MARKING	ORDERING NUMBER	TRANSPORT MEDIA, QUANTITY
THS770012	VQFN-24	RGE	–40°C to +85°C	THS770012IRGE	THS770012IRGET	Tape and reel, 250
				THS770012IRGE	THS770012IRGER	Tape and reel, 3000

- (1) For the most current package and ordering information see the Package Option Addendum at the end of this document, or visit the device product folder on www.ti.com.

Figure 3. DEVICE MARKING INFORMATION



ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Over operating free-air temperature range, unless otherwise noted.

		THS770012	UNIT
Power supply (V_{S+} to GND)		5.5	V
Input voltage range		Ground to V_{S+}	V
Differential input voltage, V_{ID}		Ground to V_{S+}	V
Continuous input current, I_I		10	mA
Continuous output current, I_O		100	mA
Storage temperature range, T_{stg}		–65°C to +150°C	°C
Maximum junction temperature, T_J		+150	°C
Maximum junction temperature, continuous operation, long term reliability		+125	°C
ESD ratings	Human body model (HBM)	2500	V
	Charged device model (CDM)	1000	V
	Machine model (MM)	100	V

- (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

THERMAL INFORMATION

THERMAL METRIC ⁽¹⁾		THS770012	UNITS
		RGE (24) PINS	
θ_{JA}	Junction-to-ambient thermal resistance	44.1	°C/W
$\theta_{JC(top)}$	Junction-to-case(top) thermal resistance	35	
θ_{JB}	Junction-to-board thermal resistance	19	
Ψ_{JT}	Junction-to-top characterization parameter	0.5	
Ψ_{JB}	Junction-to-board characterization parameter	18.8	
$\theta_{JC(bottom)}$	Junction-to-case(bottom) thermal resistance	8.9	

(1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

ELECTRICAL CHARACTERISTICS

Test conditions are at $T_A = +25^{\circ}\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, and input and output referenced to midsupply, unless otherwise noted. Measured using evaluation module as discussed in [Test Circuits](#) section.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT	TEST LEVEL ⁽¹⁾
AC PERFORMANCE						
Small-signal bandwidth	Gain = +10dB, $V_{OUT} = 200\text{mV}_{PP}$		900		MHz	C
	Gain = +11dB, $V_{OUT} = 200\text{mV}_{PP}$		810		MHz	C
	Gain = +12dB, $V_{OUT} = 200\text{mV}_{PP}$		680		MHz	C
	Gain = +13.7dB, $V_{OUT} = 200\text{mV}_{PP}$		540		MHz	C
Large-signal bandwidth	Gain = +10dB, $V_{OUT} = 2V_{PP}$		845		MHz	C
	Gain = +11dB, $V_{OUT} = 2V_{PP}$		790		MHz	C
	Gain = +12dB, $V_{OUT} = 2V_{PP}$		680		MHz	C
	Gain = +13.7dB, $V_{OUT} = 2V_{PP}$		548		MHz	C
Bandwidth for 0.1dB flatness	Gain = +12dB, $V_{OUT} = 2V_{PP}$		130		MHz	C
Slew rate	$V_{OUT} = 2\text{V}$ step		3300		V/ μs	C
	$V_{OUT} = 4\text{V}$ step		3400		V/ μs	C
Rise time	$V_{OUT} = 2\text{V}$ step		0.6		ns	C
Fall time	$V_{OUT} = 2\text{V}$ step		0.6		ns	C
Settling time to 0.1%	$V_{OUT} = 2\text{V}$ step		2.2		ns	C
Input return loss, s11	See s-Parameters section, $f < 200\text{MHz}$		-18		dB	C
Output return loss, s22	See s-Parameters section, $f < 200\text{MHz}$		-16		dB	C
Reverse isolation, s12	See s-Parameters section, $f < 200\text{MHz}$		-60		dB	C
Second-order harmonic distortion, Gain = +12dB, $R_L = 400\Omega$, $V_{OUT} = 2V_{PP}$	$f = 10\text{MHz}$		-90		dBc	C
	$f = 50\text{MHz}$		-70		dBc	C
	$f = 100\text{MHz}$		-73		dBc	C
	$f = 200\text{MHz}$		-74		dBc	C
Third-order harmonic distortion, Gain = +12dB, $R_L = 400\Omega$, $V_{OUT} = 2V_{PP}$	$f = 10\text{MHz}$		-100		dBc	C
	$f = 50\text{MHz}$		-85		dBc	C
	$f = 100\text{MHz}$		-84		dBc	C
	$f = 200\text{MHz}$		-73		dBc	C
Second-order intermodulation distortion, Gain = +12dB, $R_L = 400\Omega$, $V_{OUT} = 2V_{PP}$	$f = 50\text{MHz}$, 10MHz spacing		-62		dBc	C
	$f = 100\text{MHz}$, 10MHz spacing		-76		dBc	C
	$f = 150\text{MHz}$, 10MHz spacing		-78		dBc	C
	$f = 200\text{MHz}$, 10MHz spacing		-78		dBc	C

(1) Test levels: (A) 100% tested at $+25^{\circ}\text{C}$. Over-temperature limits by characterization and simulation. (B) Limits set by characterization and simulation. (C) Typical value only for information.

ELECTRICAL CHARACTERISTICS (continued)

Test conditions are at $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, and input and output referenced to midsupply, unless otherwise noted. Measured using evaluation module as discussed in [Test Circuits](#) section.

PARAMETER	TEST CONDITIONS		MIN	TYP	MAX	UNIT	TEST LEVEL ⁽¹⁾
Third-order intermodulation distortion, Gain = +12dB, R _L = 400Ω, V _{OUT} = 2V _{PP}	f = 50MHz, 10MHz spacing			−97		dBc	C
	f = 100MHz, 10MHz spacing			−100		dBc	C
	f = 150MHz, 10MHz spacing			−92		dBc	C
	f = 200MHz, 10MHz spacing			−81		dBc	C
1dB compression point	f = 100MHz	R _L = 20Ω		19.6		dBm	C
		R _L = 400Ω		8.7		dBm	C
Output third-order intercept point	At device outputs, R _L = 400Ω, f = 100MHz			47		dBm	C
Input-referred voltage noise	f = 1MHz			1.5		nV/√Hz	C
Opout-referred voltage noise	f = 1MHz			6		nV/√Hz	C
Noise figure	100Ω differential source	f = 50 MHz		9.5		dB	C
		f = 100 MHz		10.7		dB	C
		f = 200 MHz		12.3		dB	C
Overdrive recovery	Overdrive = ±0.5V			5	7.5	ns	B
Output balance error	f = 200MHz			-60		dB	C
Output impedance	f = 100MHz			4		Ω	C
DC PERFORMANCE							
Gain (+12dB gain setting)	T _A = +25°C, R _L = 400Ω		11.65	11.9	12.15	dB	A
	T _A = +25°C, R _L = 100Ω		11.4	11.6	11.85	dB	B
	T _A = −40°C to +85°C, R _L = 400Ω		11.6		12.2	dB	B
	T _A = −40°C to +85°C, R _L = 100Ω		11.6		12.2	dB	B
Output offset	T _A = +25°C		−20	±2	20	mV	A
	T _A = −40°C to +85°C		−22.5		22.5	mV	B
Common-mode rejection ratio	T _A = +25°C		36	60		dB	A
	T _A = −40°C to +85°C		35			dB	B
INPUT							
Differential input resistance			85	100	115	Ω	A
Input common-mode range	Inputs shorted together, V _{OCM} = 2.5V		2.25		2.75	V	A
OUTPUT							
Most positive output voltage	Each output with 200Ω to midsupply	T _A = +25°C	3.64	3.7		V	A
		T _A = −40°C to +85°C	3.59			V	B
Least positive output voltage	Each output with 200Ω to midsupply	T _A = +25°C		1.3	1.4	V	A
		T _A = −40°C to +85°C			1.45	V	B
Most positive output voltage	Each output with 50Ω to midsupply	T _A = +25°C	3.59	3.6		V	A
		T _A = −40°C to +85°C	3.54			V	B
Least positive output voltage	Each output with 50Ω to midsupply	T _A = +25°C		1.3	1.5	V	A
		T _A = −40°C to +85°C			1.55	V	B
Differential output voltage	T _A = +25°C, R _L = 400Ω		4.4	4.8		V _{PP}	B
	T _A = −40°C to +85°C, R _L = 400Ω		4.2			V _{PP}	B
Differential output current drive	T _A = +25°C, R _L = 10Ω			80		mA	B
	T _A = −40°C to +85°C, R _L =10Ω			80		mA	B


ELECTRICAL CHARACTERISTICS (continued)

Test conditions are at $T_A = +25^{\circ}\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, and input and output referenced to midsupply, unless otherwise noted. Measured using evaluation module as discussed in [Test Circuits](#) section.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT	TEST LEVEL ⁽¹⁾
OUTPUT COMMON-MODE VOLTAGE CONTROL						
V_{OCM} small-signal bandwidth	$V_{OUT_CM} = 200\text{mV}_{PP}$		300		MHz	C
V_{OCM} slew rate	$V_{OUT_CM} = 500\text{mV}$ step		150		V/ μs	C
V_{OCM} voltage range	Supplied by external source ⁽²⁾	2.25	2.5	2.75	V	C
V_{OCM} gain	$V_{OCM} = 2.5\text{V}$	0.98	1	1.02	V/V	A
Output common-mode offset from V_{OCM} input	$V_{OCM} = 2.5\text{V}$	–30	± 12	30	mV	A
V_{OCM} input bias current	$2.25\text{V} \leq V_{OCM} \leq 2.75\text{V}$	–400	± 30	400	μA	A
POWER SUPPLY						
Specified operating voltage		4.75	5	5.25	V	C
Quiescent current	$T_A = +25^{\circ}\text{C}$	85	100	115	mA	A
	$T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$	80		125	mA	B
Power-supply rejection ratio	$T_A = +25^{\circ}\text{C}$, $V_{S+} = 5\text{V} \pm 0.25\text{V}$	60	90		dB	A
	$T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, $V_{S+} = 5\text{V} \pm 0.5\text{V}$	59			dB	B
POWER-DOWN						
Enable voltage threshold	Device powers on below 0.5V			0.5	V	A
Disable voltage threshold	Device powers down above 2.0V	2			V	A
Power-down quiescent current			0.8	3	mA	A
Input bias current			80	100	μA	A
Turn-on time delay	Time to $V_{OUT} = 90\%$ of final value		10		μs	C
Turn-off time delay	Time to $V_{OUT} = 10\%$ of original value		0.15		μs	C
THERMAL CHARACTERISTICS						
Specified operating range		–40		+85	$^{\circ}\text{C}$	C
Thermal resistance, θ_{JC} ⁽³⁾	Junction to case (bottom)		8.9		$^{\circ}\text{C}/\text{W}$	C
Thermal resistance, θ_{JA} ⁽³⁾	Junction to ambient		44.1		$^{\circ}\text{C}/\text{W}$	C

- (2) Limits set by best harmonic distortion with $V_{OUT} = 3V_{PP}$. V_{OCM} voltage range can be extended if lower output swing is used or distortion degradation is allowed, and increased bias current into pin is acceptable. For more information, see [Figure 18](#) and [Figure 34](#).
- (3) Tested using JEDEC High-K test PCB. Thermal management of the final printed circuit board (PCB) should keep the junction temperature below $+125^{\circ}\text{C}$ for long term reliability.

PIN CONFIGURATION



PIN DESCRIPTIONS

PIN		DESCRIPTION
NO.	NAME	
1	NC	No internal connection
2	PD	Power down. High = low power (sleep) mode. Low = active.
3	V _{IN-}	Inverting input pin
4	V _{IN+}	Non-inverting input pin
5	V _{OCM}	Output common-mode voltage control input pin
6, 7	NC	No internal connection
8, 9, 10, 11	GND	Ground. Must be connected to thermal pad.
12	NC	No internal connection
13	GS-	Gain-setting connection for inverting output
14	Unused	Bonded to die, but not used. Tie to GND.
15	V _{OUT-}	Inverting output pin
16	V _{OUT+}	Non-inverting output pin
17	Unused	Bonded to die, but not used. Tie to GND.
18	GS+	Gain-setting connection for non-inverting output
19	NC	No internal connection
20, 21, 22, 23	V _{S+}	Power supply pins, +5V nominal
24	NC	No internal connection
Thermal pad		Thermal pad on bottom of device is used for heat dissipation and must be tied to GND

TYPICAL CHARACTERISTICS

TABLE OF GRAPHS

TITLE	FIGURE
200mV _{pp} Frequency Response Magnitude	Figure 4
200mV _{pp} Frequency Response Phase	Figure 5
2V _{pp} Frequency Response Magnitude	Figure 6
2V _{pp} Frequency Response Phase	Figure 7
3V _{pp} Frequency Response Magnitude	Figure 8
3V _{pp} Frequency Response Phase	Figure 9
Small- and Large-Signal Pulse Response	Figure 10
Slew Rate vs Output Voltage Step	Figure 11
Overdrive Recovery	Figure 12
Single-Ended Input Harmonic Distortion vs Frequency	Figure 13
Harmonic Distortion vs Frequency	Figure 14
Harmonic Distortion vs Output Voltage	Figure 15
Harmonic Distortion vs Load	Figure 16
Harmonic Distortion vs Gain	Figure 17
Harmonic Distortion vs Output Common-Mode Voltage	Figure 18
Intermodulation Distortion vs Frequency	Figure 19
Output Intercept Point vs Frequency	Figure 20
Maximum Differential Output Voltage Swing Peak-to-Peak vs Differential Load Resistance	Figure 21
Maximum/Minimum Single-Ended Output Voltage vs Differential Load Resistance	Figure 22
Differential Output Impedance vs Frequency	Figure 23
Frequency Response vs Capacitive Load	Figure 24
Recommended Output Resistance vs Capacitive Load	Figure 25
Common-Mode Rejection Ratio vs Frequency	Figure 26
Power-Supply Rejection Ratio vs Frequency	Figure 27
Turn-On Time	Figure 28
Turn-Off Time	Figure 29
Input and Output Voltage Noise vs Frequency	Figure 30
Output Balance Error vs Frequency	Figure 31
V _{OCM} Small-Signal Frequency Response	Figure 32
Output Common-Mode Pulse Response	Figure 33
V _{OCM} Input Bias Current vs V _{OCM} Input Voltage	Figure 34
s-Parameters (Magnitude)	Figure 35
Noise Figure vs Frequency	Figure 36

TYPICAL CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.

200mV_{PP} FREQUENCY RESPONSE MAGNITUDE




Figure 4.

200mV_{PP} FREQUENCY RESPONSE PHASE




Figure 5.

2V_{PP} FREQUENCY RESPONSE MAGNITUDE




Figure 6.

2V_{PP} FREQUENCY RESPONSE PHASE




Figure 7.

3V_{PP} FREQUENCY RESPONSE MAGNITUDE




Figure 8.

3V_{PP} FREQUENCY RESPONSE PHASE




Figure 9.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.




Figure 10.




Figure 11.




Figure 12.




Figure 13.




Figure 14.




Figure 15.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.

**HARMONIC DISTORTION
vs LOAD**




Figure 16.

**HARMONIC DISTORTION
vs GAIN**




Figure 17.

**HARMONIC DISTORTION
vs OUTPUT COMMON-MODE VOLTAGE**




Figure 18.

**INTERMODULATION DISTORTION
vs FREQUENCY**




Figure 19.

**OUTPUT INTERCEPT POINT
vs FREQUENCY**




Figure 20.

**MAXIMUM DIFFERENTIAL OUTPUT VOLTAGE SWING
PEAK-TO-PEAK vs DIFFERENTIAL LOAD RESISTANCE**




Figure 21.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.

**MAXIMUM/MINIMUM SINGLE-ENDED OUTPUT VOLTAGE
vs DIFFERENTIAL LOAD RESISTANCE**




Figure 22.

**DIFFERENTIAL OUTPUT IMPEDANCE
vs FREQUENCY**




Figure 23.

**FREQUENCY RESPONSE
vs CAPACITIVE LOAD**




Figure 24.

**RECOMMENDED OUTPUT RESISTANCE
vs CAPACITIVE LOAD**




Figure 25.

**COMMON-MODE REJECTION RATIO
vs FREQUENCY**




Figure 26.

**POWER-SUPPLY REJECTION RATIO
vs FREQUENCY**




Figure 27.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.

TURN-ON TIME




Figure 28.

TURN-OFF TIME




Figure 29.


INPUT AND OUTPUT VOLTAGE NOISE
vs FREQUENCY

Figure 30.


OUTPUT BALANCE ERROR
vs FREQUENCY

Figure 31.


 V_{OCM} SMALL-SIGNAL FREQUENCY RESPONSE

Figure 32.

OUTPUT COMMON-MODE PULSE RESPONSE




Figure 33.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{S+} = +5\text{V}$, $V_{OCM} = +2.5\text{V}$, $V_{OUT} = 2V_{PP}$, $R_L = 400\Omega$ differential, $G = +12\text{dB}$, differential input and output, input and output pins referenced to midsupply, unless otherwise noted. Measured using EVM as discussed in [Test Circuits](#) section.

**V_{OCM} INPUT BIAS CURRENT
vs V_{OCM} INPUT VOLTAGE**




Figure 34.

**s-PARAMETERS
(MAGNITUDE)**




Figure 35.

**NOISE FIGURE
vs FREQUENCY**



Figure 36.

TEST CIRCUITS

OVERVIEW

The standard THS770012 evaluation module (EVM) is used for testing the typical performance shown in the Typical Characteristics, with changes as noted below. The EVM schematic is shown in [Figure 37](#). The signal generators and analyzers used for most tests have single-ended 50Ω input and output impedance. The THS770012 EVM is configured to convert to and from a single-ended 50Ω impedance by using RF transformers or baluns 1:1 (CX2156NL from Pulse, supplied as a standard configuration of the EVM) to allow easy connection to standard lab equipment. For line input termination, two 49.9Ω resistors (R5 and R6) are placed to ground on the input transformer output pins (terminals 1 and 3). In combination with the 100Ω input impedance of the device, the total impedance seen by the line is 50Ω.

Gain is set by placing external components R11, R12, R13, and R14 as described below in [Setting the Gain](#) section.

A resistor network is used on the amplifier output to present various loads (R_L) and maintain line output termination to 50Ω. Depending on the test conditions, component values are changed as shown in [Table 1](#), or as otherwise noted. As a result of the voltage divider on the output formed by the load component values, the amplifier output is attenuated. The *Loss* column in [Table 1](#) shows the attenuation expected from the resistor divider. The output transformer causes slightly more loss, so these numbers are approximate.

Table 1. Load Component Values⁽¹⁾

LOAD R_L	R15 AND R17	R16	LOSS
100Ω	25Ω	Open	6dB
200Ω	86.6Ω	69.8Ω	16.8dB
400Ω	187Ω	57.6Ω	25.5dB
1kΩ	487Ω	52.3Ω	31.8dB

- (1) The total load includes 50Ω termination by the test equipment. Components are chosen to achieve load and 50Ω line termination through a 1:1 transformer.




Figure 37. THS770012IRGE EVM Schematic

TEST DESCRIPTIONS

The following sections describe how the tests were performed, as well as the EVM circuit modifications that were made (if any). Modifications made for test purposes include changing capacitors to resistors, resistors to capacitors, the shorting/opening of components, etc., as noted. Unless otherwise noted, C1, C2, C9, and C13 are all changed to 0.1 μ F to give basically flat frequency response from below 1MHz to the bandwidth of the amplifier, and gain is set to nominal +12dB.

Frequency Response: 200mV_{PP}, 2V_{PP}, 3V_{PP}

The test is run on the standard EVM using the transformers in the signal path.

A network analyzer is connected to the input and output of the EVM with 50 Ω coaxial cables and set to measure the forward transfer function (s21). The input signal frequency is swept with signal level set for desired output amplitude.

The test ran for gains of +10dB, +11dB, +12dB and +13.7dB with component values changed per [Table 2](#) in [Setting the Gain](#) section.

s-Parameters: s11, s22, and s12

The standard EVM is used with both R15 and R17 = 24.9 Ω , and R16 = open, to test the input return loss, output return loss, and reverse isolation. A network analyzer is connected to the input and output of the EVM with 50 Ω coaxial cables and set to measure the appropriate transfer function: s11, s22, or s12. Note the transformers are included in the signal chain in order to retrieve proper measurements with single-ended test equipment. The impact is minimal from 10MHz to 200MHz, but further analysis is required to fully de-embed the respective effects.

Frequency Response with Capacitive Load

The standard EVM is used with R15 and R17 = R_O, R16 = C_{LOAD}, C9 and C13 = 953 Ω , R21 = open, T2 removed, and jumpers placed across terminals 3 to 4 and 1 to 6. A network analyzer is connected to the input and output of the EVM with 50 Ω coaxial cables and set to measure the forward transfer function (s21). Different values of load capacitance are placed on the output (at R16) and the output resistor values (R15 and R17) changed until an optimally flat frequency response is achieved with maximum bandwidth.

Distortion

The standard EVM is used for measurement of single-tone harmonic distortion and two-tone intermodulation distortion. For differential distortion measurements, the standard EVM is used with no modification. For single-ended input distortion measurements, the standard EVM is used with T1 removed and jumpers placed across terminals 3 to 4 and 1 to 6, and R5 and R6 = 100 Ω . A signal generator is connected to the J1 input of the EVM with 50 Ω coaxial cables, with filters inserted inline to reduce distortion from the generator. The J3 output of the EVM is connected with 50 Ω coaxial cables to a spectrum analyzer to measure the fundamental(s) and distortion products.

Noise Figure

The standard EVM is used with T1 changed to a 1:2 impedance ratio transformer (Mini-Circuits ADT2), R15 and R17 = 24.9 Ω , and R5, R6, and R16 = open. A noise figure analyzer is connected to the input and output of the EVM with 50 Ω coaxial cables. The noise figure analyzer provides a 50 Ω (noise) source so that the data are adjusted to refer to a 100 Ω source.

Transient Response, Slew Rate, Overdrive Recovery

The standard EVM is used with T1 and T2 removed and jumpers placed across terminals 3 to 4 and 1 to 6; R15, R17, and R25 = 49.9 Ω ; C1, C2, C9, and C13 = 0 Ω ; and R5, R6, R16, and R21 = open. A differential waveform generator is connected to the input of the EVM with 50 Ω coaxial cables at J1 and J2. The differential output at J3 and J4 is connected with 50 Ω coaxial cables to an oscilloscope to measure the outputs. Waveform math in the oscilloscope is used to combine the differential output of the device.

Power-Down

The standard EVM is used with T1 and T2 removed, jumpers placed across terminals 3 to 4 and 1 to 6, R15 and R17 = 49.9Ω, C9 and C13 = 0Ω, and R5, R6, R16, and R21 = open. A waveform generator is connected to the power-down input of the EVM with a 50Ω coaxial cable at J8. The differential output at J3 and J4 is connected with 50Ω coaxial cables to an oscilloscope to measure the outputs. J1 is left disconnected so that the output is driven to the V_{OCM} voltage when the device is active, and discharged through the resistive load on the output when disabled. Both outputs are the same and only one is shown.

Differential Z-out

The standard EVM is used with R15 and R17 = 24.9Ω, and R16 = open. A network analyzer is connected to the output of the EVM at J3 with 50Ω coaxial cable, both inputs are terminated with a 50Ω load, and a high-impedance differential probe is used for the measurement. The analyzer is set to measure the forward transfer function (s21). The analyzer with probe input is calibrated across the open resistor pads of R16 and the signal is measured at the output pins of the device. The output impedance is calculated using the known resistor values and the attenuation caused by R15 and R17.

Output Balance Error

The standard EVM is used with R15 and R17 = 100Ω, and R16 = 0Ω. A network analyzer is connected to the input of the EVM with 50Ω coaxial cable, the output is left open, and a high-impedance differential probe is used for the measurement. The analyzer is set to measure the forward transfer function (s21). The analyzer with probe input is calibrated at the input pins of the device and the signal is measured from the shorted pads of R16 to ground.

Common-Mode Rejection

The standard EVM is used with T1 removed and jumpers place across terminals 3 to 4, 1 to 6, and 1 to 3. A network analyzer is connected to the input and output of the EVM with 50Ω coaxial cable and set to measure the forward transfer function (s21).

V_{OCM} Frequency Response

The standard EVM is used with T2 removed and jumpers across terminals 3 to 4 and 1 to 6; R10, R15, and R17 = 49.9Ω; C3 and C4 = 0Ω; and R9, R16, and R21 = open. A network analyzer is connected to the V_{OCM} input of the EVM at J7 and output of the EVM with 50Ω coaxial cable, and set to measure the forward transfer function (s21). The input signal frequency is swept with the signal level set for 200mV. Each output at J3 and J4 is measured as single-ended, and because both are the same, only one output is shown.

V_{OCM} Slew Rate and Pulse Response

The standard EVM is used with T2 removed and jumpers across terminals 3 to 4 and 1 to 6; R10, R15, and R17 = 49.9Ω; C9 and C13 = 0Ω; and C3, C4, R9, R16, and R21 = open. A waveform generator is connected to the V_{OCM} input of the EVM at J7 with 50Ω coaxial cable. The differential output at J3 and J4 is connected with 50Ω coaxial cable to an oscilloscope to measure the outputs. J1 is left disconnected so that the output is driven to the V_{OCM} voltage. Both outputs are the same, so only one is shown.

Input/Output Voltage Noise, Settling Time, and Power-Supply Rejection

These parameters are taken from simulation.

THEORY OF OPERATION

GENERAL DESCRIPTION

The THS770012 is a wideband, fully differential amplifier designed and optimized specifically for driving 14-bit and 16-bit ADCs at input frequencies up to 200MHz. This device provides high bandwidth, low distortion, and low noise, which are critical parameters in high-speed data acquisition systems that require very high dynamic range, such as wireless base stations and test and measurement applications. It also makes an excellent differential amplifier for general-purpose, high-speed differential signal chain and short line-driver applications. The device has an operating power-supply range of 4.75V to 5.5V. The THS770012 has proprietary circuitry to provide very fast recovery from overdrive conditions and has a power-down mode for power saving. The THS770012 is offered in a Pb-free (RoHS compliant) and green, QFN-24 thermally-enhanced package. It is characterized for operation over the industrial temperature range of -40°C to $+85^{\circ}\text{C}$.

The amplifier uses two negative-feedback loops. One is for the primary differential amplifier and the other controls the common-mode operation.

Primary Differential Amplifier

The primary amplifier of the THS770012 is a fully-differential op amp with on-chip gain setting resistors. The gain of the device can be changed by using external components as described in [Setting the Gain](#) section below. The nominal gain with no external connections is set to +12dB with $R_F = 200\Omega$ and $R_G = 50\Omega$.

V_{OCM} Control Loop

The output common-mode voltage is controlled through a second negative-feedback loop. The output common-mode voltage is internally sensed and compared to the V_{OCM} pin. The loop then works to drive the difference, or error voltage, to zero in order to maintain the output common-mode voltage = V_{OCM} (within the loop gain and bandwidth of the loop). For more details on fully-differential amplifier theory and use, see application report [SLOA054, Fully-Differential Amplifiers](#), available for download from www.ti.com.

OPERATION

Differential to Differential

The THS770012 is a fully-differential amplifier that can be used to amplify differential input signals to differential output signals. A basic block diagram of the circuit with nominal gain of +12dB is shown in [Figure 38](#). The differential input to differential output configuration gives the best performance; the signal source and load should be balanced.




Figure 38. Differential Input to Differential Output Amplifier

Single-Ended to Differential

The THS770012 can be used to amplify and convert single-ended input signals to differential output signals. A basic block diagram of the circuit with nominal gain of +12dB is shown in Figure 39. In order to maintain proper balance in the amplifier and avoid offsets at the output, the alternate input must be biased and the impedance matched to the signal input. For example, if a 50Ω source biased to 2.5V provides the input, the alternate input should be tied to 2.5V through 50Ω. If a 50Ω source is ac-coupled to the input, the alternate input should be ac-coupled to ground through 50Ω. Note that the ac coupling should provide a similar frequency response to balance the gain over frequency.




Figure 39. Single-Ended Input to Differential Output Amplifier

Setting the Gain

Gain is adjustable by placing external components in positions R11, R12, R13, and R14 on the EVM. Table 2 below shows the component values for setting gain from +10dB to +13.7dB. The different configurations and values change the effective value of the internal feedback, where the gain is determined by the resultant effective R_F/R_G , where $R_G = 50\Omega$

Table 2. Gain Settings

GAIN	R11, R12	R13, R14	EFFECTIVE R_F
+10dB	Open	140 Ω	$140 \parallel 340 + 60 = 159 \Omega$
+11dB	Open	523 Ω	$140 \parallel 723 + 60 = 177 \Omega$
+12dB	Open	Open	$140 + 60 = 200 \Omega$
+13.7dB (AC gain), +12dB (DC gain) ⁽¹⁾	0.1 μ F capacitors	Open	$\frac{(140 \parallel 200 + 60) \times (140 + 200)}{200} = 242 \Omega$

(1) Using 0.1 μ F capacitors for R11 and R12 limits the low frequency response to the default value of +12dB at frequency below about 10kHz. For +13.7dB gain at DC, connect pins 13 and 18 of the device to a low impedance voltage source equal to V_{OCM} (+2.5V nominal).

Setting the Output Common-Mode Voltage

The V_{OCM} input controls the output common-mode voltage. V_{OCM} has no internal biasing network and must be driven by an external source or resistor divider network to the positive power supply. In ac-coupled applications, the V_{OCM} input impedance and bias current are not critical, but in dc-coupled applications where more accuracy is desired, the input bias current of the pin should be considered. For best harmonic distortion with $V_{OUT} = 3V_{PP}$, the V_{OCM} input should be maintained within the operating range of 2.25V to 2.75V. The V_{OCM} input voltage can be operated outside this range if lower output swing is used or distortion degradation is allowed, and increased bias current into the pin is acceptable. For more information, see Figure 18 and Figure 34. It is recommended to use a 0.1 μ F decoupling capacitor from the V_{OCM} pin to ground to prevent noise and other spurious signals from coupling into the common-mode loop of the amplifier.

Input Common-Mode Voltage Range

The THS770012 is designed primarily for ac-coupled operation. With input dc blocking, the input common-mode voltage of the device is driven to the same voltage as V_{OCM} by the outputs. Therefore, as long as the V_{OCM} input is maintained within the operating range of 2.25V to 2.75V, the input common-mode of the main amplifier is also maintained within its linear operating range of 2.25V to 2.75V. If the device is used with dc coupled input, the driving source needs to bias the input to its linear operating range of 2.25V to 2.75V for proper operation.

Operation with Split Supply $\pm 2.5\text{V}$

The THS770012 can be operated using a split $\pm 2.5\text{V}$ supply. In this case, V_{S+} is connected to $+2.5\text{V}$, and GND (and any other pin noted to be connected to GND) is connected to -2.5V . As with any device, the THS770012 is impervious to what the user decides to name the levels in the system. In essence, it is simply a level shift of the power pins by -2.5V . If everything else is level-shifted by the same amount, the device sees no difference. With a $\pm 2.5\text{V}$ power supply, the V_{OCM} range is $0\text{V} \pm 0.25\text{V}$; therefore, power-down levels are $-2.5\text{V} = \text{on}$ and $+2.5\text{V} = \text{off}$, and input and output voltage ranges are symmetrical about 0V . This design has certain advantages in systems where signals are referenced to ground, and as noted in the following section, for driving ADCs with low input common-mode voltage requirements in dc-coupled applications.

Driving Capacitive Loads

The THS770012 is tested as described previously, with the data shown in the typical graphs. Due to the internal gain resistor architecture used on the device, the only practical means to avoid stability problems such as overshoot/ringing, gain peaking, and oscillation when driving capacitive loads is to place small resistors in series with the outputs (R_O) to isolate the phase shift caused by the capacitive load from the feedback loop of the amplifier. Note there are 2Ω internal resistors in series with each output to help maintain stability. The Typical Characteristics graphs show recommended values for an optimally flat frequency response with maximum bandwidth. Smaller values of R_O can be used if more peaking is allowed, and larger values can be used to - reduce the bandwidth.

Driving ADCs

The THS770012 is designed and optimized for the highest performance to drive differential input ADCs. Figure 40 shows a generic block diagram of the THS770012 driving an ADC. The primary interface circuit between the amplifier and the ADC is usually a filter of some type for antialias purposes, and provides a means to bias the signal to the input common-mode voltage required by the ADC. Filters range from single-order real RC poles to higher-order LC filters, depending on the requirements of the application. Output resistors (R_O) are shown on the amplifier outputs to isolate the amplifier from any capacitive loading presented by the filter.




Figure 40. Generic ADC Driver Block Diagram

The key points to consider for implementation are described in the following three subsections.

SNR Considerations

The signal-to-noise ratio (SNR) of the amplifier + filter + ADC adds in RMS fashion. Noise from the amplifier is bandwidth-limited by the filter. Depending on the amplitude of the signal and the bandwidth of the filter, the SNR of the amplifier + filter can be calculated. To get the combined SNR, this value is then squared, added to the square of the ADC SNR, and the square-root is taken. If the SNR of the amplifier + filter equals the SNR of the ADC, the combined SNR is 3dB higher and for minimal impact on the ADC's SNR the SNR of the amplifier + filter should be 10dB or more lower. The combined SNR calculated in this manner is usually accurate to within $\pm 1\text{dB}$ of actual implementation.

SFDR Considerations

Theoretically, the spurious-free dynamic range (SFDR) of the amplifier + filter + ADC adds linearly on a spur-by-spur basis. The amplifier output spurs are linearly related solely to the input signal and the SFDR is usually set by second-order or third-order harmonic distortion for single-tone inputs, and by second-order or third-order intermodulation distortion for two-tone inputs. Harmonic and second-order intermodulation distortion can be filtered to some degree by the antialias filter, but not third-order intermodulation distortion. Generally, the ADC also has the same distortion products, but as a result of the sampling nature and potential for clock feedthrough, there may be spurs not linearly related solely to the input signal. When the spurs from the amplifier + filter are known, each can be directly added to the same spur from the ADC. This is a worst-case analysis based on the assumption the spurs sources are in phase. If the spur of the amplifier + filter equals the spur of the ADC, the combined spur is 6dB higher. The combined spur calculated in this manner is usually accurate to within $\pm 6\text{dB}$ of actual implementation, but higher variations have been observed especially in second-order performance as a result of phase shift in the filter.

Common-mode phase shift introduced by the filter nullifies the basic assumption that the spur sources are in phase. This phase shift can lead to better performance than predicted as the spurs become phase shifted, and there is the potential for cancellation as the phase shift reaches 180° .

Differential phase and magnitude imbalance in the filter as a result of mismatched components caused by nominal tolerance can severely degrade the second-order distortion of the ADC. Single-order RC filters cause very little differential phase shift with nominal tolerances of 5% or less, but higher-order LC filters are very sensitive to component mismatch. For instance, a third-order Butterworth bandpass filter with 100MHz center frequency and 20MHz bandwidth shows up to 20° differential phase imbalance in a Spice Monte Carlo analysis with 2% component tolerances. Therefore, while a prototype may work, production variance is unacceptable. Low tolerance 1% components and low order filter is recommended for best performance. Otherwise a transformer or balun is recommended at the ADC input to restore the phase balance in the input signal to the ADC.

ADC Input Common-Mode Voltage Considerations

The input common-mode voltage range of the ADC must be observed for proper operation. In an ac-coupled application between the amplifier and the ADC, the input common-mode voltage bias of the ADC is accomplished in different ways depending on the ADC. Some use internal bias networks and others use external components, such as resistors, from each input to the CM output of the ADC. When ac coupling, the output common-mode voltage of the amplifier is a *don't care* for the ADC, and V_{OCM} should be set for optimum performance of the amplifier.

DC-coupled applications vary in complexity and requirements, depending on the ADC. Devices such as the [ADS5424](#) require a nominal 2.4V input common-mode, while others such as the [ADS5485](#) require a nominal 3.1V input common-mode, and still others like the [ADS6149](#) require 1.5V and the [ADS4149](#) require 0.95V. Given the THS770012 output common-mode range, ADCs with input common-mode closer to 2.5V are easier to dc-couple to, and require little or no level shifting. For applications that require a different common-mode voltage between the amplifier and the ADC, a resistor network can be used, as shown in [Figure 41](#). With ADCs that have internal resistors (R_{INT}) that bias the ADC input to V_{CM} , the bias resistors do not affect the desired value of R_p , but do cause more attenuation of the differential input signal. Knowing the differential input resistance is required and sometimes, that is all that is provided.




Figure 41. Resistor Network to DC Level Shift Common-Mode Voltage

For common-mode analysis, assume that $V_{AMP\pm} = V_{OCM}$ and $V_{ADC\pm} = V_{ADC}$ (the specification for the ADC input common-mode voltage). V_{REF} is chosen to be a voltage within the system (such as the ADC or amplifier analog supply) or ground, depending on whether the voltage must be pulled up or down, and R_O is chosen to be a reasonable value, such as 49.9Ω . With these known values, R_P can be found by using [Equation 1](#):

$$R_P = R_O \left(\frac{V_{ADC} - V_{REF}}{V_{AMP} - V_{ADC}} \right) \quad (1)$$

The insertion of this resistor network also attenuates the amplifier output signal. The gain (or loss) can be calculated by [Equation 2](#):

$$GAIN = \left(\frac{2R_P \parallel Z_{IN}}{2R_O + 2R_P \parallel Z_{IN}} \right) \quad (2)$$

Using the gain and knowing the full-scale input of the ADC, $V_{ADC\ FS}$, the required amplitude to drive the ADC with the network can be calculated using [Equation 3](#):

$$V_{AMP\ PP} = \frac{V_{ADC\ FS}}{GAIN} \quad (3)$$

Using the ADC examples given previously, [Table 3](#) shows sample calculations of the value of R_P and $V_{AMP\ FS}$ for full-scale drive, and then for $-1dB$ (often times, the ADC drive is backed off from full-scale in applications, so lower amplitudes may be acceptable). All voltages are in volts, resistors in Ω (the nearest standard value should be used), and gain as noted. [Table 3](#) does not include the ADS5424 because no level shift is required with this device.

Table 3. Example R_P for Various ADCs

ADC	V_{OCM} (V_{DC})	V_{ADC} (V_{DC})	V_{REF} (V_{DC})	R_{INT} (Ω)	R_O (Ω)	R_P (Ω)	GAIN (V/V)	GAIN (dB)	$V_{ADC\ FS}$ (V_{PP})	$V_{AMP\ PP}$ FS (V_{PP})	$V_{AMP\ PP}$ -1dBFS (V_{PP})
ADS5485	2.5	3.1	5	1k	50	158.3	0.73	-2.71	2	4.10	3.65
ADS6149	2.5	1.5	0	NA	50	75.0	0.60	-4.44	2	3.33	2.97
ADS4149	2.5	0.95	0	NA	50	30.6	0.38	-8.40	2	5.26	4.69
ADS4149	0 ⁽¹⁾	0.95	2.5	NA	50	81.6	0.62	-4.15	2	3.23	2.88

(1) THS770012 with $\pm 2.5V$ supply.

The calculated values for the ADS5485 give the lowest attenuation, and because of the high V_{FS} , it requires $3.65V_{PP}$ from the amplifier to drive to $-1dBFS$. Performance of the THS770012 is still very good up to 130MHz at this level, but the designer may want to further back off from full-scale for best performance and consider trading reduced SNR performance for better SFDR performance.

The values calculated for the ADS6149 show reasonable design targets and should work with good performance. Note the ADS6149 does not have buffered inputs, and the inputs have equivalent resistive impedance that varies with sampling frequency. In order to account for the increased loss, half of this resistance should be used for the value of R_{INT} in [Equation 2](#).

The values calculated for the low input common-mode of the ADS4149 result in large attenuation of the amplifier signal leading to $5.26V_{PP}$ being required for full-scale ADC drive. This amplitude is greater than the maximum capability of the device. With a single +5V supply, the THS770012 is not suitable to drive this ADC in dc-coupled applications unless the ADC input is backed off towards $-6dBFS$. Another option is to operate the THS770012 with a split $\pm 2.5V$ supply, and is shown in the last row of [Table 3](#). For this situation, if the +2.5V is used as the pull-up voltage, only $2.88V_{PP}$ is required for the $-1dBFS$ input to the ADS4149. See the [Operation with Split Supply \$\pm 2.5V\$](#) section for more detail. Note that the ADS4149 does not have buffered inputs and the inputs have equivalent resistive impedance that varies with sampling frequency. In order to account for the increased loss, half of this resistance should be used for the value of R_{INT} in [Equation 2](#).

As with any design, testing is recommended to validate whether it meets the specific design goals.

APPLICATION INFORMATION

THS770012 DRIVING 16-BIT ADC

To illustrate the performance of the THS770012 as an ADC driver, the device is tested with a 16-bit ADC.

For testing purposes, a 30MHz, second-order Butterworth bandpass filter with center frequency at 100MHz is designed. The design target for the source impedance is 40Ω differential, and for load impedance is 400Ω differential. Therefore, approximately 1dB insertion loss is expected in the pass-band, requiring the amplifier output amplitude to be 2.5V_{PP} to drive the ADC to –1dBFS.

The output noise voltage specification for the THS770012 is 6 nV/√Hz. With 2.5V_{PP} amplifier output voltage swing and 30MHz bandwidth, the expected SNR from the amplifier + antialias filter is 88.5dBc. When added in combination with the 16-bit ADC, the expected total SNR is 75.2dBFS for the typical case.

Figure 42 shows the resulting FFT plot when driving the ADC to –1dBFS with a single-tone 95MHz sine wave, and sampling at 130MSPS. Test results show 100dBc SFDR from the forth-order harmonic and 74.4 dBFS SNR; analysis of the plot is shown in Table 4 versus typical ADC specifications. The test results from circuit board to circuit board shows over 10dB of variation in the second order harmonic due to component tolerance. Using lower 1% tolerance components or adding a balun between the filter and ADC inputs resulted in less variation and the typical expected results should be better than 95dBc SFDR and 74dB SNR.




Figure 42. FFT Plot of THS770012 + 30MHz BPF + 16-Bit ADC with 95MHz Single-Tone Input Sampling at 130MSPS

Table 4. Analysis of FFT for THS770012 + BPF + 16-Bit ADC at 95MHz vs Typical ADC Specifications

CONFIGURATION	ADC INPUT	SNR	HD2	HD3
THS770012 + BPF + 16Bit ADC	–1dBFS	74.4dBFS	–101dBc	–101dBc
16-Bit ADC Only (typ)	–1dBFS	75.2dBFS	–100dBc	–100dBc

EVM AND LAYOUT RECOMMENDATIONS

Figure 37 is the THS770012RGE EVM schematic, and Figure 43 through Figure 46 show the layout details of the EVM PCB. Table 5 is the bill of materials for the EVM as supplied from TI. It is recommended to follow the layout of the external components as close as possible to the amplifier, ground plane construction, and power routing. General layout guidelines are:

1. Place a 2.2μF to 10μF capacitor on each supply pin within 2 inches from the device. It can be shared among other op amps.
2. Place a 0.01μF to 0.1μF capacitor on each supply pin to ground as close as possible to the device. Placement within 1mm of the device supply pins ensures best performance.
3. Keep output traces as short as possible to minimize parasitic capacitance and inductance. Doing so reduces unwanted characteristics such as peaking in the frequency response, overshoot, and ringing in the pulse response, and results in a more stable design.
4. To reduce parasitic capacitance, ground plane and power-supply planes should be removed from device output pins.
5. The V_{OCM} pin must be biased to a voltage between 2.25V to 2.75V for proper operation. Place a 0.1μF to 0.22μF capacitor to ground as close as possible to the device to prevent noise coupling into the common-mode.
6. For best performance, drive circuits and loads should be balanced and biased to keep the input and output common-mode voltage between 2.25V to 2.75V. AC-coupling is a simple way to achieve this performance.
7. The THS770012 is provided in a thermally enhanced PowerPAD™ package. The package is constructed using a downset leadframe on which the die is mounted. This arrangement results in low thermal resistance to the thermal pad on the underside of the package. Excellent thermal performance can be achieved by following the guidelines in TI application reports [SLMA002, PowerPAD™ Thermally-Enhanced Package](#) and [SLMA004, PowerPAD™ Made Easy](#). For proper operation, the thermal pad on the bottom of the device must be tied to the same voltage potential as the GND pin on the device.




Figure 43. EVM Layout: Top Layer




Figure 44. EVM Layout: Bottom Layer




Figure 45. EVM Layout: Layer 2




Figure 46. EVM Layout: Layer 3

Table 5. THS770012RGE EVM Bill of Materials

ITEM	DESCRIPTION	SMD SIZE	REFERENCE DESIGNATOR	QTY	MANUFACTURER PART NUMBER	DISTRIBUTOR PART NUMBER
1	CAP, 10.0uF, CERAMIC, X7R, 10V	1206	C4, C5, C6	3	(TDK) C3216X7R1A106K	(DIGI-KEY) 445-4043-1-ND
2	CAP, 0.1uF, CERAMIC, X7R, 16V	0603	C7, C8	2	(AVX) 0603YC104KAT2A	(DIGI-KEY) 478-1239-1-ND
3	CAP, 0.01uF, CERAMIC, X7R, 16V	0402	C10, C11	2	(AVX) 0402YC103KAT2A	(DIGI-KEY) 478-1114-1-ND
4	CAP, 100pF, CERAMIC, NPO, 50V	0402	C12	1	(AVX) 04025A101KAT2A	(DIGI-KEY) 478-4979-1-ND
5	CAP, 1000pF, CERAMIC, X7R, 50V	0402	C1, C2, C3, C9, C13	5	(AVX) 04025C102KAT2A	(DIGI-KEY) 478-1101-1-ND
6	OPEN	0402	R11, R12, R13, R14	4		
7	RESISTOR, 0 OHM	0402	R4, R21	2	(PANASONIC) ERJ-2GE0R00X	(DIGI-KEY) P0.0JCT-ND
8	RESISTOR, 49.9 OHM, 1/10W, 1%	0402	R5, R6	2	(PANASONIC) ERJ-2RKF49R9X	(DIGI-KEY) P49.9LCT-ND
9	RESISTOR, 57.6 OHM, 1/10W, 1%	0402	R16	1	(PANASONIC) ERJ-2RKF57R6X	(DIGI-KEY) P57.6LCT-ND
10	RESISTOR, 187 OHM, 1/10W, 1%	0402	R15, R17	2	(PANASONIC) ERJ-2RKF1870X	(DIGI-KEY) P187LCT-ND
11	RESISTOR, 1K OHM, 1/10W, 1%	0402	R9, R10	2	(PANASONIC) ERJ-2RKF1001X	(DIGI-KEY) P1.00KLCT-ND
12	RESISTOR, 10K OHM, 1/10W, 1%	0603	R25, R26	2	(PANASONIC) ERJ-3EKF1002V	(DIGI-KEY) P10.0KHCT-ND
13	TRANSFORMER, BALUN		T1, T2	2	(PULSE) CX2156NL	(DIGI-KEY) 553-1499-ND
14	JACK, BANANA RECEPTANCE, 0.25" DIA. HOLE		J5, J6	3	(SPC) 15459	(NEWARK) 79K5034
15	CONNECTOR, SMA PCB JACK		J7, J8	2	(AMPHENOL) 901-144-8RFX	(NEWARK) 34C8151
16	CONNECTOR, EDGE, SMA PCB JACK		J1, J2, J3, J4	4	(JOHNSON) 142-0701-801	(NEWARK) 90F2624
17	HEADER, 0.1" CTRS, 0.025" SQ. PINS	3 POS.	JP1, JP2	2	(SULLINS) PBC36SAAN	(DIGI-KEY) S1011E-36-ND
18	SHUNTS		JP1, JP2	2	(SULLINS) SSC02SYAN	(DIGI-KEY) S9002-ND
19	TEST POINT, RED		TP3	1	(KEYSTONE) 5000	(DIGI-KEY) 5000K-ND
20	TEST POINT, BLACK		TP1, TP2	2	(KEYSTONE) 5001	(DIGI-KEY) 5001K-ND
21	IC, THS770012		U1	1	(TI) THS770012RGE	
22	STANDOFF, 4-40 HEX, 0.625" LENGTH			4	(KEYSTONE) 1808	(DIGI-KEY) 1808K-ND
23	SCREW, PHILLIPS, 4-40, .250"			4	PMSSS 440 0025 PH	(DIGI-KEY) H703-ND
24	BOARD, PRINTED CIRCUIT				(TI) EDGE# 6515711 REV.A	

Evaluation Board/Kit Important Notice

Texas Instruments (TI) provides the enclosed product(s) under the following conditions:

This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. Persons handling the product(s) must have electronics training and observe good engineering practice standards. As such, the goods being provided are not intended to be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including product safety and environmental measures typically found in end products that incorporate such semiconductor components or circuit boards. This evaluation board/kit does not fall within the scope of the European Union directives regarding electromagnetic compatibility, restricted substances (RoHS), recycling (WEEE), FCC, CE or UL, and therefore may not meet the technical requirements of these directives or other related directives.

Should this evaluation board/kit not meet the specifications indicated in the User's Guide, the board/kit may be returned within 30 days from the date of delivery for a full refund. **THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.**

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user indemnifies TI from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge.

EXCEPT TO THE EXTENT OF THE INDEMNITY SET FORTH ABOVE, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

TI currently deals with a variety of customers for products, and therefore our arrangement with the user **is not exclusive**.

TI assumes **no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein.**

Please read the User's Guide and, specifically, the Warnings and Restrictions notice in the User's Guide prior to handling the product. This notice contains important safety information about temperatures and voltages. For additional information on TI's environmental and/or safety programs, please contact the TI application engineer or visit www.ti.com/esh.

No license is granted under any patent right or other intellectual property right of TI covering or relating to any machine, process, or combination in which such TI products or services might be or are used.

FCC Warning

This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. It generates, uses, and can radiate radio frequency energy and has not been tested for compliance with the limits of computing devices pursuant to part 15 of FCC rules, which are designed to provide reasonable protection against radio frequency interference. Operation of this equipment in other environments may cause interference with radio communications, in which case the user at his own expense will be required to take whatever measures may be required to correct this interference.

EVM Warnings and Restrictions

It is important to operate this EVM within the input voltage range of 0V to +5.5V and the output voltage range of 0V to +5.5V.

Exceeding the specified input range may cause unexpected operation and/or irreversible damage to the EVM. If there are questions concerning the input range, please contact a TI field representative prior to connecting the input power.

Applying loads outside of the specified output range may result in unintended operation and/or possible permanent damage to the EVM. Please consult the EVM User's Guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative.

During normal operation, some circuit components may have case temperatures greater than +85°C. The EVM is designed to operate properly with certain components above +85°C as long as the input and output ranges are maintained. These components include but are not limited to linear regulators, switching transistors, pass transistors, and current sense resistors. These types of devices can be identified using the EVM schematic located in the EVM User's Guide. When placing measurement probes near these devices during operation, please be aware that these devices may be very warm to the touch.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2012, Texas Instruments Incorporated

REVISION HISTORY

Changes from Revision A (November 2010) to Revision B	Page
- Changed to Revision B, May 2011 - Deleted "using a.....have changes" from THS770012 Driving ADS5493 section last part of the first sentence - Deleted paragraphs, Figure 39 and section title under the first bulleted lists of THS770012 Driving ADS5493 section. Also deleted the next section title and "and bulit on the EVM" in the sentence under the title.	1 23 23
Changes from Revision B (May 2011) to Revision C	Page
Deleted all ADS5493 information	1

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
THS770012IRGER	ACTIVE	VQFN	RGE	24	3000	Green (RoHS & no Sb/Br)	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	THS7700 12IRGE	Samples
THS770012IRGET	ACTIVE	VQFN	RGE	24	250	Green (RoHS & no Sb/Br)	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	THS7700 12IRGE	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.



(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION
REEL DIMENSIONS

TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

TAPE AND REEL INFORMATION

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
THS770012IRGER	VQFN	RGE	24	3000	330.0	12.4	4.25	4.25	1.15	8.0	12.0	Q2
THS770012IRGET	VQFN	RGE	24	250	180.0	12.4	4.25	4.25	1.15	8.0	12.0	Q2

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
THS770012IRGER	VQFN	RGE	24	3000	367.0	367.0	35.0
THS770012IRGET	VQFN	RGE	24	250	210.0	185.0	35.0

RGE 24

GENERIC PACKAGE VIEW



VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.

4204104/H



4219013/A 05/2017

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.

EXAMPLE BOARD LAYOUT


RGE0024B

VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:15X



SOLDER MASK DETAILS

4219013/A 05/2017

NOTES: (continued)


- This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/sluea271).
- Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.

EXAMPLE STENCIL DESIGN

RGE0024B

VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD 25
78% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE
SCALE:20X

4219013/A 05/2017

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2020, Texas Instruments Incorporated