

SIZE	QTY	SYM	PLTD
70	2	+	NPLTD
95	8	X	PLTD
10	40	□	PLTD

FAB DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON ANGLE ±1 2 PLACE ±.01 3 PLACE ±.005 INTERPRET DIM AND TOL PER ASME Y14.5M - 1994		APPROVALS <table border="1"> <tr> <th>DRAWN</th> <th>INIT</th> <th>DATE</th> </tr> <tr> <td>CHECK</td> <td></td> <td></td> </tr> <tr> <td>DESIGN</td> <td>JUNE WU</td> <td>11/6/03</td> </tr> <tr> <td>ENGR</td> <td>Keith S.</td> <td>11/6/03</td> </tr> </table>		DRAWN	INIT	DATE	CHECK			DESIGN	JUNE WU	11/6/03	ENGR	Keith S.	11/6/03	LINEAR TECHNOLOGY 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE															
CHECK																	
DESIGN	JUNE WU	11/6/03															
ENGR	Keith S.	11/6/03															
TITLE: LT13434IEF 60V 3A 200kHz Step-Down Converter with Burst Mode™				SIZE A DEMO DC614A REV. A													
SCALE = NONE				DES-230581 SHT 1 of 1													

NOTES : Unless Otherwise Specified


- FAB PER IPC-A-600.
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISHED ON OUTER LAYERS.
1 OZ. COPPER FINISHED ON INNER LAYERS.
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
- SIZE: DIMENSIONS AND TOLERANCES SHOWN.
0.000 ARE PRIMARY DATUMS.
- DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER. .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
- FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.

WHITE TIN IMMERSION (OMIKRON) BOTH SIDES.

6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.

7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.

8. SCORING:



REVISIONS		
REV	DESCRIPTION	DATE