



NOTES: UNLESS OTHERWISE SPECIFIED

1. FAB PER IPC-A-600.
2. MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
 - FINISHED THICKNESS TO BE 0.062 +/- .005
 - TOTAL OF 6 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
 - FLAMMABILITY RATING: 94 V-0 MINIMUM.
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
4. DRILLING: -DRILL HOLES PER SCHEDULE PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.
 - ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
 - HOLE LOCATION TOLERANCES ARE +/-0.003 IN RELATION TO CENTER
5. FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN.
 - GOLD IMMERSION BOTH SIDES.
 - FOR SILKScreens: USE WHITE NON-CONDUCTIVE INK.
6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE. PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
7. PCBs ARE TO BE RoHS COMPLIANT.
8. SCORING FOR PANELIZED PCB (PRODUCTION FAB ONLY):



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: 0.XX = ± 0.01 0.XXX = ± 0.005 INTERPRET DIM AND TOL PER ASME Y14.5M-1994 THIRD ANGLE PROJECTION	APPROVALS		 <div>1630 MCARTHY BLVD SUITE 205 PH: (408) 432-1900 WWW.LINEAR.COM LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY</div>		
	PCB DES.	HZ			
	APP ENG.	YI S.			
	TITLE: FABRICATION DRAWING				
	SINGLE PHASE DC/DC CONVERTER WITH INPUT CURRENT SENSE				
	SIZE	IC NO.	LTC3883EUH	FAMILY	REV
	N/A		DEMO	CIRCUIT	1778B 1
	SCALE = NOME		FIL NAME:		DC1778B-1PCB SHT 1 OF 1

SIZE	QTY	SYM	PLATED	TOL
0.187	4	+	N0	+/-0.003
0.067	22	×	YES	+/-0.003
0.035	21	□	YES	+/-0.003
0.01	319	⊗	YES	+/-0.003
0.205	2	⊗	YES	+/-0.003
0.189	2	⊥ ^A	YES	+/-0.003
0.055	5	⊥ ^B	YES	+/-0.003
0.037	26	⊥ ^C	YES	+/-0.003
0.03543	6	⊥ ^D	YES	+/-0.003
0.0315	2	⊥ ^E	YES	+/-0.003