

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

FAIRCHILD SEMICONDUCTOR™

June 2002
Revised March 2004

NC7SP14
TinyLogic® ULP Inverter with Schmitt Trigger Input

General Description

The NC7SP14 is a single inverter with Schmitt trigger input from Fairchild's Ultra Low Power (ULP) Series of TinyLogic®. Ideal for applications where battery life is critical, this product is designed for ultra low power consumption within the V_{CC} operating range of 0.9V to 3.6V V_{CC}.

The internal circuit is composed of a minimum of inverter stages, including the output buffer, to enable ultra low static and dynamic power.

The NC7SP14, for lower drive requirements, is uniquely designed for optimized power and speed, and is fabricated with an advanced CMOS technology to achieve best in class speed operation while maintaining extremely low CMOS power dissipation.


Features

- 0.9V to 3.6V V_{CC} supply operation
- 3.6V overvoltage tolerant I/O's at V_{CC} from 0.9V to 3.6V
- t_{PD}
  - 4.0 ns typ for 3.0V to 3.6V V_{CC}
  - 5.0 ns typ for 2.3V to 2.7V V_{CC}
  - 6.0 ns typ for 1.65V to 1.95V V_{CC}
  - 7.0 ns typ for 1.40V to 1.60V V_{CC}
  - 11.0 ns typ for 1.10V to 1.30V V_{CC}
  - 27.0 ns typ for 0.90V V_{CC}
- Power-Off high impedance inputs and outputs
- Static Drive (I_{OH}/I_{OL})
  - ±2.6 mA @ 3.00V V_{CC}
  - ±2.1 mA @ 2.30V V_{CC}
  - ±1.5 mA @ 1.65V V_{CC}
  - ±1.0 mA @ 1.40V V_{CC}
  - ±0.5 mA @ 1.10V V_{CC}
  - ±20 μA @ 0.9V V_{CC}
- Uses patented Quiet Series™ noise/EMI reduction circuitry
- Ultra small MicroPak™ leadfree package
- Ultra low dynamic power

Ordering Code:

Order Number	Package Number	Product Code Top Mark	Package Description	Supplied As
NC7SP14P5X	MAA05A	P14	5-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3k Units on Tape and Reel
NC7SP14L6X	MAC06A	K3	6-Lead MicroPak, 1.0mm Wide	5k Units on Tape and Reel

Battery Life vs. V_{CC} Supply Voltage




TinyLogic ULP and ULP-A with up to 50% less power consumption can extend your battery life significantly.
Battery Life = $(V_{battery} * I_{battery} * .9)/(P_{device})/24$hrs/day
Where, $P_{device} = (I_{CC} * V_{CC}) + (C_{PD} + C_L) * V_{CC}^2 * f$
Assumes ideal 3.6V Lithium Ion battery with current rating of 900mAH and derated 90% and device frequency at 10MHz, with C_L = 15 pF load

TinyLogic® is a registered trademark, and Quiet Series™, and MicroPak™ are trademarks of Fairchild Semiconductor Corporation.

Logic Symbol

IEEE/IEC



Pin Descriptions

Pin Names	Description
A	Input
Y	Output
NC	No Connect

Function Table


$Y = \overline{A}$

Inputs	Output
A	**Y**
L	H
H	L

H = HIGH Logic Level
L = LOW Logic Level


Connection Diagrams

Pin Assignments for SC70



(Top View)

Pad Assignments for MicroPak



(Top Thru View)

Absolute Maximum Ratings (Note 1)

Supply Voltage (V_{CC})	−0.5V to +4.6V
DC Input Voltage (V_{IN})	−0.5V to +4.6V
DC Output Voltage (V_{OUT})	
HIGH or LOW State (Note 2)	−0.5V to V_{CC} +0.5V
V_{CC} = 0V	−0.5V to 4.6V
DC Input Diode Current (I_{IK}) V_{IN} < 0V	±50 mA
DC Output Diode Current (I_{OK})	
V_{OUT} < 0V	−50 mA
V_{OUT} > V_{CC}	+50 mA
DC Output Source/Sink Current (I_{OH}/I_{OL})	± 50 mA
DC V_{CC} or Ground Current per	
Supply Pin (I_{CC} or Ground)	± 50 mA
Storage Temperature Range (T_{STG})	−65°C to +150°C

Recommended Operating Conditions (Note 3)

Supply Voltage	0.9V to 3.6V
Input Voltage (V_{IN})	0.0V to 3.6V
Output Voltage (V_{OUT})	
HIGH or LOW State	0V to V_{CC}
V_{CC} = 0V	0V to 3.6V
Output Current in I_{OH}/I_{OL}	
V_{CC} = 3.0V to 3.6V	±2.6 mA
V_{CC} = 2.3V to 2.7V	± 2.1 mA
V_{CC} = 1.65V to 1.95V	± 1.5 mA
V_{CC} = 1.40V to 1.60V	± 1 mA
V_{CC} = 1.10V to 1.30V	±0.5 mA
V_{CC} = 0.9V	±20 µA
Free Air Operating Temperature (T_A)	−40°C to +85°C
Minimum Input Edge Rate ($\Delta t/\Delta V$)	
V_{IN} = 0.8V to 2.0V, V_{CC} = 3.0V	10 ns/V

Note 1: Absolute Maximum Ratings: are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: I_O Absolute Maximum Rating must be observed.

Note 3: Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	T_A = +25°C		T_A = −40°C to +85°C		Units	Conditions
			Min	Max	Min	Max		
V_P	Positive Threshold Voltage	0.90	0.3	0.6	0.3	0.6	V	
		1.10	0.4	1.0	0.4	1.0		
		1.40	0.5	1.2	0.5	1.2		
		1.65	0.7	1.5	0.7	1.5		
		2.30	1.0	1.9	1.0	1.9		
		3.00	1.5	2.6	1.5	2.6		
V_N	Negative Threshold Voltage	0.90	0.1	0.6	0.1	0.6	V	
		1.10	0.15	0.7	0.15	0.7		
		1.40	0.2	0.8	0.2	0.8		
		1.65	0.25	0.9	0.25	0.9		
		2.30	0.4	1.15	0.4	1.15		
		3.00	0.6	1.5	0.6	1.5		
V_H	Hysteresis Voltage	0.90	0.07	0.5	0.07	0.5	V	
		1.10	0.08	0.6	0.08	0.6		
		1.40	0.09	0.8	0.09	0.8		
		1.65	0.10	1.0	0.10	1.0		
		2.30	0.25	1.1	0.25	1.1		
		3.00	0.60	1.8	0.60	1.8		

DC Electrical Characteristics (Continued)

Symbol	Parameter	V_{CC} (V)	$T_A = +25°C$		$T_A = -40°C$ to $+85°C$		Units	Conditions
			Min	Max	Min	Max		
V_{OH}	HIGH Level Output Voltage	0.90	V_{CC} – 0.1		V_{CC} – 0.1		V	I_{OH} = –20 μA
		1.10 ≤ V_{CC} ≤ 1.30	V_{CC} – 0.1		V_{CC} – 0.1			
		1.40 ≤ V_{CC} ≤ 1.60	V_{CC} – 0.1		V_{CC} – 0.1			
		1.65 ≤ V_{CC} ≤ 1.95	V_{CC} – 0.1		V_{CC} – 0.1			
		2.30 ≤ V_{CC} ≤ 2.70	V_{CC} – 0.1		V_{CC} – 0.1			
		3.00 ≤ V_{CC} ≤ 3.60	V_{CC} – 0.1		V_{CC} – 0.1			
		1.10 ≤ V_{CC} ≤ 1.30	0.75 x V_{CC}		0.70 x V_{CC}			I_{OH} = –0.5 mA
		1.40 ≤ V_{CC} ≤ 1.60	1.07		0.99			I_{OH} = –1 mA
		1.65 ≤ V_{CC} ≤ 1.95	1.24		1.22			I_{OH} = –1.5 mA
		2.30 ≤ V_{CC} ≤ 2.70	1.95		1.87			I_{OH} = –2.1 mA
		3.00 ≤ V_{CC} ≤ 3.60	2.61		2.55			I_{OH} = –2.6 mA
V_{OL}	LOW Level Output Voltage	0.90		0.1		0.1	V	I_{OL} = 20 μA
		1.10 ≤ V_{CC} ≤ 1.30		0.1		0.1		
		1.40 ≤ V_{CC} ≤ 1.60		0.1		0.1		
		1.65 ≤ V_{CC} ≤ 1.95		0.1		0.1		
		2.30 ≤ V_{CC} ≤ 2.70		0.1		0.1		
		3.00 ≤ V_{CC} ≤ 3.60		0.1		0.1		
		1.10 ≤ V_{CC} ≤ 1.30		0.30 x V_{CC}		0.30 x V_{CC}		I_{OL} = 0.5 mA
		1.40 ≤ V_{CC} ≤ 1.60		0.31		0.37		I_{OL} = 1 mA
		1.65 ≤ V_{CC} ≤ 1.95		0.31		0.35		I_{OL} = 1.5 mA
		2.30 ≤ V_{CC} ≤ 2.70		0.31		0.33		I_{OL} = 2.1 mA
		3.00 ≤ V_{CC} ≤ 3.60		0.31		0.33		I_{OL} = 2.6 mA
I_{IN}	Input Leakage Current	0.90 to 3.60		±0.1		±0.5	μA	0 ≤ V_I ≤ 3.6V
I_{OFF}	Power Off Leakage Current	0		0.5		0.5	μA	0 ≤ (V_I, V_O) ≤ 3.6V
I_{CC}	Quiescent Supply Current	0.90 to 3.60		0.9		0.9	μA	V_I = V_{CC} or GND

AC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	$T_A = +25°C$			$T_A = -40°C$ to $+85°C$		Units	Conditions	Figure Number
			Min	Typ	Max	Min	Max			
t_{PHL}	Propagation Delay	0.90		27				ns	C_L = 10 pF R_L = 1 MΩ	Figures 1, 2
t_{PLH}		1.10 ≤ V_{CC} ≤ 1.30	3.5	11	21.8	3.0	34.3			
		1.40 ≤ V_{CC} ≤ 1.60	2.5	7	14.8	2.0	15.0			
		1.65 ≤ V_{CC} ≤ 1.95	2.0	6	12.0	1.5	12.2			
		2.30 ≤ V_{CC} ≤ 2.70	1.5	5	9.4	1.0	9.9			
		3.00 ≤ V_{CC} ≤ 3.60	1.0	4	8.3	1.0	9.0			
t_{PHL}	Propagation Delay	0.90		30				ns	C_L = 15 pF R_L = 1 MΩ	Figures 1, 2
t_{PLH}		1.10 ≤ V_{CC} ≤ 1.30	4.0	11	22.8	3.5	37.3			
		1.40 ≤ V_{CC} ≤ 1.60	3.0	8	15.5	2.5	16.5			
		1.65 ≤ V_{CC} ≤ 1.95	2.5	6	12.6	2.0	13.6			
		2.30 ≤ V_{CC} ≤ 2.70	2.0	5	9.9	1.5	10.8			
		3.00 ≤ V_{CC} ≤ 3.60	1.5	4	8.7	1.0	9.5			
t_{PHL}	Propagation Delay	0.90		32				ns	C_L = 30 pF R_L = 1 MΩ	Figures 1, 2
t_{PLH}		1.10 ≤ V_{CC} ≤ 1.30	5.0	13	25.9	4.0	46.3			
		1.40 ≤ V_{CC} ≤ 1.60	4.0	9	17.8	3.5	18.2			
		1.65 ≤ V_{CC} ≤ 1.95	3.0	7	14.4	2.0	15.9			
		2.30 ≤ V_{CC} ≤ 2.70	2.0	6	11.3	1.5	12.8			
		3.00 ≤ V_{CC} ≤ 3.60	1.5	5	9.2	1.0	10.7			
C_{IN}	Input Capacitance	0		2.0				pF		
C_{OUT}	Output Capacitance	0		4.0				pF		
C_{PD}	Power Dissipation Capacitance	0.9 to 3.60		8				pF	V_I = 0V or V_{CC}, f = 10 MHz	

AC Loading and Waveforms




FIGURE 1. AC Test Circuit




FIGURE 2. AC Waveforms


Symbol	V_{CC}					
	3.3V ± 0.3V	**2.5V ± 0.2V**	**1.8V ± 0.15V**	**1.5V ± 0.10V**	**1.2V ± 0.10V**	**0.9V**
V_{mi}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$
V_{mo}	1.5V	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$	$V_{CC}/2$


Tape and Reel Specification

TAPE FORMAT for SC70


Package Designator	Tape Section	Number Cavities	Cavity Status	Cover Tape Status
P5X	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed

TAPE DIMENSIONS inches (millimeters)






SECTION B–B



SECTION A–A




BEND RADIUS NOT TO SCALE

Tape and Reel Specification (Continued)


TAPE FORMAT for MicroPak

Package Designator	Tape Section	Number Cavities	Cavity Status	Cover Tape Status
L6X	Leader (Start End)	125 (typ)	Empty	Sealed
	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (typ)	Empty	Sealed

TAPE DIMENSIONS inches (millimeters)




REEL DIMENSIONS inches (millimeters)



Tape Size	A	B	C	D	N	W1	W2	W3
8 mm	7.0 (177.8)	0.059 (1.50)	0.512 (13.00)	0.795 (20.20)	2.165 (55.00)	0.331 + 0.059/–0.000 (8.40 + 1.50/–0.00)	0.567 (14.40)	W1 + 0.078/–0.039 (W1 + 2.00/–1.00)

Physical Dimensions inches (millimeters) unless otherwise noted




NOTES:

A. CONFORMS TO EIAJ REGISTERED OUTLINE DRAWING SC88A.
B. DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH.
C. DIMENSIONS ARE IN MILLIMETERS.

MAA05ARevC

5-Lead SC70, EIAJ SC-88a, 1.25mm Wide
Package Number MAA05A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Notes:

1. JEDEC PACKAGE REGISTRATION IS ANTICIPATED
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y14.5M-1994

MAC06ARevB

6-Lead MicroPak, 1.0mm Wide
Package Number MAC06A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative