Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

April 2014

FDPC8014S

PowerTrench® Power Clip
25V Asymmetric Dual N-Channel MOSFET

Features

Q1: N-Channel

- Max $r_{DS(on)}$ = 3.8 mΩ at V_{GS} = 10 V, I_D = 20 A
- Max $r_{DS(on)}$ = 4.7 mΩ at V_{GS} = 4.5 V, I_D = 18 A

Q2: N-Channel

- Max $r_{DS(on)}$ = 1.2 mΩ at V_{GS} = 10 V, I_D = 41 A
- Max $r_{DS(on)}$ = 1.4 mΩ at V_{GS} = 4.5 V, I_D = 37 A
- Low inductance packaging shortens rise/fall times, resulting in lower switching losses
- MOSFET integration enables optimum layout for lower circuit inductance and reduced switch node ringing
- RoHS Compliant

General Description

This device includes two specialized N-Channel MOSFETs in a dual package. The switch node has been internally connected to enable easy placement and routing of synchronous buck converters. The control MOSFET (Q1) and synchronous SyncFET™ (Q2) have been designed to provide optimal power efficiency.

Applications

- Computing
- Communications
- General Purpose Point of Load



Pin	Name	Description	Pin	Name	Description	Pin	Name	Description
1	HSG	High Side Gate	3,4,10	V+(HSD)	High Side Drain	8	LSG	Low Side Gate
2	GR	Gate Return	5,6,7	SW	Switching Node, Low Side Drain	9	GND(LSS)	Low Side Source

MOSFET Maximum Ratings T_A = 25 °C unless otherwise noted

Symbol	Parameter		Q1	Q2	Units
V_{DS}	Drain to Source Voltage		25[Note5]	25	V
V_{GS}	Gate to Source Voltage		±12	±12	V
I_D	Drain Current -Continuous	T_C = 25 °C	60	110	A
	-Continuous	T_A = 25 °C	20[Note1a]	41[Note1b]	
	-Pulsed	T_A = 25 °C (Note 4)	75	160	
E_{AS}	Single Pulse Avalanche Energy	(Note 3)	73	253	mJ
P_D	Power Dissipation for Single Operation	T_C = 25 °C	21	42	W
	Power Dissipation for Single Operation	T_A = 25 °C	2.1[Note1a]	2.3 [Note1b]	
T_J, T_{STG}	Operating and Storage Junction Temperature Range		-55 to +150		°C

Thermal Characteristics

$R_{\theta JC}$	Thermal Resistance, Junction to Case	6.0	3.0	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	60[Note1a]	55[Note1b]	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	130[Note1c]	120[Note1d]	

©2013 Fairchild Semiconductor Corporation

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
05OD/16OD	FDPC8014S	Power Clip 56	13 ”	12 mm	3000 units

Electrical Characteristics T_J = 25 °C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
Off Characteristics							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V I_D = 1 mA, V_{GS} = 0 V	Q1 Q2	25 25			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25 °C I_D = 10 mA, referenced to 25 °C	Q1 Q2		24 24		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 20 V, V_{GS} = 0 V V_{DS} = 20 V, V_{GS} = 0 V	Q1 Q2			1 500	μA μA
I_{GSS}	Gate to Source Leakage Current, Forward	V_{GS} = 12 V/-8 V, V_{DS}= 0 V V_{GS} = 12 V/-8 V, V_{DS}= 0 V	Q1 Q2			±100 ±100	nA nA
On Characteristics							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA V_{GS} = V_{DS}, I_D = 1 mA	Q1 Q2	0.8 1.1	1.3 1.4	2.5 2.5	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25 °C I_D = 10 mA, referenced to 25 °C	Q1 Q2		-4 -3		mV/°C
$r_{DS(on)}$	Drain to Source On Resistance	V_{GS} = 10V, I_D = 20 A V_{GS} = 4.5 V, I_D = 18 A V_{GS} = 10 V, I_D = 20 A,T_J =125 °C	Q1		2.8 3.4 3.9	3.8 4.7 5.3	mΩ
		V_{GS} = 10V, I_D = 41 A V_{GS} = 4.5 V, I_D = 37 A V_{GS} = 10 V, I_D = 41 A ,T_J =125 °C	Q2		0.9 1.0 1.1	1.2 1.4 1.5	
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 20 A V_{DS} = 5 V, I_D = 41 A	Q1 Q2		182 315		S
Dynamic Characteristics							
C_{iss}	Input Capacitance	Q1: V_{DS} = 13 V, V_{GS} = 0 V, f = 1 MHZ Q2: V_{DS} = 13 V, V_{GS} = 0 V, f = 1 MHZ	Q1 Q2		1695 6580	2375 9870	pF
C_{oss}	Output Capacitance		Q1 Q2		495 1720	710 2580	pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2		54 204	100 370	pF
R_g	Gate Resistance		Q1 Q2	0.1 0.1	0.4 0.4	1.2 1.2	Ω
Switching Characteristics							
$t_{d(on)}$	Turn-On Delay Time	Q1: V_{DD} = 13 V, I_D = 20 A, R_{GEN} = 6 Ω Q2: V_{DD} = 13 V, I_D = 41 A, R_{GEN} = 6 Ω	Q1 Q2		8 16	16 28	ns
t_r	Rise Time		Q1 Q2		2 6	10 11	ns
$t_{d(off)}$	Turn-Off Delay Time		Q1 Q2		24 47	38 75	ns
t_f	Fall Time		Q1 Q2		2 4	10 10	ns
Q_g	Total Gate Charge	V_{GS} = 0 V to 10 V Q1 V_{DD} = 13 V, I_D = 20 A Q2 V_{DD} = 13 V, I_D = 41 A	Q1 Q2		25 93	35 130	nC
Q_g	Total Gate Charge	V_{GS} = 0 V to 4.5 V	Q1 Q2		11 43	16 60	nC
Q_{gs}	Gate to Source Gate Charge		Q1 Q2		3.4 13		nC
Q_{gd}	Gate to Drain “Miller” Charge		Q1 Q2		2.2 8.5		nC

Electrical Characteristics T_J = 25 °C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
Drain-Source Diode Characteristics							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 20 A (Note 2) V_{GS} = 0 V, I_S = 41 A (Note 2)	Q1 Q2		0.8 0.8	1.2 1.2	V
I_S	Diode continuous forward current	T_C = 25 °C	Q1 Q2		60 110		A
$I_{S,Pulse}$	Diode pulse current		Q1 Q2		75 160		A
t_{rr}	Reverse Recovery Time	Q1 I_F = 20 A, di/dt = 100 A/µs	Q1 Q2		25 36	40 58	ns
Q_{rr}	Reverse Recovery Charge	Q2 I_F = 41 A, di/dt = 300 A/µs	Q1 Q2		10 47	20 75	nC

Notes:

1.$R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



a. 60 °C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 55 °C/W when mounted on a 1 in^2 pad of 2 oz copper



c. 130 °C/W when mounted on a minimum pad of 2 oz copper



d. 120 °C/W when mounted on a minimum pad of 2 oz copper

2 Pulse Test: Pulse Width < 300 µs, Duty cycle < 2.0%.

3. Q1 :E_{AS} of 73 mJ is based on starting T_J = 25 °C; N-ch: L = 3 mH, I_{AS} = 7 A, V_{DD} = 30 V, V_{GS} = 10 V. 100% test at L= 0.1 mH, I_{AS} = 24 A.
Q2: E_{AS} of 253 mJ is based on starting T_J = 25 °C; N-ch: L = 3 mH, I_{AS} = 13 A, V_{DD} = 25 V, V_{GS} = 10 V. 100% test at L= 0.1 mH, I_{AS} = 43 A.

4. Pulsed Id limited by junction temperature,td<=10 us. Please refer to SOA curve for more details.

5. The continuous V_{DS} rating is 25 V; However, a pulse of 30 V peak voltage for no longer than 100 ns duration at 600 KHz frequency can be applied.

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 1. On Region Characteristics



Figure 2. Normalized On-Resistance vs. Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs. Junction Temperature



Figure 4. On-Resistance vs. Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs. Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs. Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 13. Junction-to-Case Transient Thermal Response Curve

Typical Characteristics (Q2 N-Channel) T_J = 25 °C unless otherwise noted



Figure 14. On- Region Characteristics



Figure 15. Normalized on-Resistance vs. Drain Current and Gate Voltage



Figure 16. Normalized On-Resistance vs. Junction Temperature



Figure 17. On-Resistance vs. Gate to Source Voltage



Figure 18. Transfer Characteristics



Figure 19. Source to Drain Diode Forward Voltage vs. Source Current

Typical Characteristics (Q2 N-Channel) T_J = 25°C unless otherwise noted



Figure 20. Gate Charge Characteristics



Figure 21. Capacitance vs. Drain to Source Voltage



Figure 22. Unclamped Inductive Switching Capability



Figure 23. Maximum Continuous Drain Current vs. Case Temperature



Figure 24. Forward Bias Safe Operating Area



Figure 25. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q2 N-Channel) T_J = 25 °C unless otherwise noted



Figure 26. Junction-to-Case Transient Thermal Response Curve

Typical Characteristics (continued)

SyncFET™ Schottky body diode Characteristics

Fairchild's SyncFET™ process embeds a Schottky diode in parallel with PowerTrench® MOSFET. This diode exhibits similar characteristics to a discrete external Schottky diode in parallel with a MOSFET. Figure 27 shows the reverses recovery characteristic of the FDPC8014S.

Schottky barrier diodes exhibit significant leakage at high temperature and high reverse voltage. This will increase the power in the device.



Figure 27. FDPC8014S SyncFET™ Body Diode Reverse Recovery Characteristic



Figure 28. SyncFET™ Body Diode Reverse Leakage vs. Drain-source Voltage



TOP VIEW



SIDE VIEW



RECOMMENDED LAND PATTERN



BOTTOM VIEW



DETAIL A
(SCALE: 2X)

NOTES: UNLESS OTHERWISE SPECIFIED

A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO-229, DATED 11/2001.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
E) DRAWING FILE NAME: PQFN08KREV2

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative