


CoolMOS™ 1) Power MOSFET


Fully isolated package
N-Channel Enhancement Mode
Low $R_{DS(on)}$, High V_{DSS} MOSFET
Ultra low gate charge

Preliminary data

$$\begin{aligned} I_{D25} &= 5.4 \text{ A} \\ V_{DSS} &= 600 \text{ V} \\ R_{DS(on) \text{ max}} &= 0.385 \Omega \end{aligned}$$



TO-220 ABFP



MOSFET			
Symbol	Conditions	Maximum Ratings	
V_{DSS}	$T_{VJ} = 25^{\circ}\text{C}$	600	V
V_{GS}		± 20	V
I_{D25}	$T_C = 25^{\circ}\text{C}$	5.4	A
I_{D90}	$T_C = 90^{\circ}\text{C}$	3.7	A
E_{AS} E_{AR}	single pulse repetitive } $I_D = 3.4 \text{ A}; T_C = 25^{\circ}\text{C}$	225 0.3	mJ mJ
dV/dt	MOSFET dV/dt ruggedness $V_{DS} = 0 \dots 480 \text{ V}$	50	V/ns

Features

- Fast CoolMOS™ 1) power MOSFET 4th generation
- High blocking capability
- Lowest resistance
- Avalanche rated for unclamped inductive switching (UIS)
- Fully isolated package

Applications

- Switched mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)
- Power factor correction (PFC)
- Welding
- Inductive heating
- PDP and LCD adapter

1) CoolMOS™ is a trademark of Infineon Technologies AG.

Symbol	Conditions	Characteristic Values			
		(T _{VJ} = 25°C, unless otherwise specified)			
		min.	typ.	max.	
$R_{DS(on)}$	$V_{GS} = 10 \text{ V}; I_D = 5.2 \text{ A}$		350	385	mΩ
$V_{GS(th)}$	$V_{DS} = V_{GS}; I_D = 0.34 \text{ mA}$	2.5	3	3.5	V
I_{DSS}	$V_{DS} = 600 \text{ V}; V_{GS} = 0 \text{ V}$			1	μA
	$T_{VJ} = 25^{\circ}\text{C}$ $T_{VJ} = 125^{\circ}\text{C}$		10		μA
I_{GSS}	$V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$			100	nA
C_{iss} C_{oss}	$V_{GS} = 0 \text{ V}; V_{DS} = 100 \text{ V}$ $f = 1 \text{ MHz}$		790 38		pF pF
Q_g Q_{gs} Q_{gd}	$V_{GS} = 0 \text{ to } 10 \text{ V}; V_{DS} = 400 \text{ V}; I_D = 5.2 \text{ A}$		17 4 6	22	nC nC nC
$t_{d(on)}$ t_r $t_{d(off)}$ t_f	$V_{GS} = 10 \text{ V}; V_{DS} = 400 \text{ V}$ $I_D = 5.2 \text{ A}; R_G = 3.3 \Omega$		10 5 40 5		ns ns ns ns
R_{thJC}				3.95	K/W

Source-Drain Diode

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
I_S	$V_{GS} = 0\text{ V}$			5.2
V_{SD}	$I_F = 5.2\text{ A}; V_{GS} = 0\text{ V}$	0.9	1.2	
t_{rr}	$I_F = 5.2\text{ A}; -di_F/dt = 100\text{ A}/\mu\text{s}; V_R = 400\text{ V}$	260		ns
Q_{RM}		21		μC
I_{RM}		24		A

Component

Symbol	Conditions	Maximum Ratings		
T _{VJ}	operating	-55...+150		°C
T _{stg}		-55...+150		°C
M _d	mounting torque	0.4 ... 0.6		Nm
Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
R _{thCH}	with heatsink compound	0.50		K/W
R _{thJA}	thermal resistance junction - ambient	80		K/W
Weight		2		g

TO-220 ABFP Outline





Fig. 1 Power dissipation




Fig. 2 Typ. output characteristics




Fig. 3 Typ. output characteristics




Fig. 3 Typ. drain-source on-state resistance characteristics of IGBT




Fig. 4 Drain-source on-state resistance




Fig. 5 Typ. transfer characteristics




Fig. 6 Forward characteristic of reverse diode




Fig. 7 Typ. gate charge




Fig. 8 Typ. capacitances




Fig. 9 Avalanche energy




Fig. 10 Drain-source breakdown voltage