

Low-Power, High-Precision Operational Amplifier

FEATURES

- Supply Current 600 μ A Max
- OP-07 Type Performance
 - Offset Voltage 25 μ V Max
 - Offset Voltage Drift 0.6 μ V/ $^{\circ}$ C Max
- Very Low Bias Current 100pA Max
- Very Low Offset Current 100pA Max
- Low Noise 0.5 μ Vp-p
- Common Mode Rejection Ratio 114dB Min

APPLICATIONS

- Replaces OP-07 While Saving Power
- Precision Instrumentation
- Charge Integrators
- Wide Dynamic Range Logarithmic Amplifiers
- Light Meters
- Low Frequency Active Filters
- Thermocouple Amplifiers

DESCRIPTION

The OP-97 is a low-power precision amplifier that provides OP-07 performance while drawing less than 1/6 the OP-07 supply current. Offset voltage is 10 μ V and drift with temperature is 0.2 μ V/ $^{\circ}$ C.


The OP-97 performance is improved over OP-07 performance in several areas. Bias and offset currents remain in the picoampere levels over the full military temperature range. Common mode voltage rejection and power supply rejection are also improved.

The OP-97 conforms to the OP-07 pinout with the null potentiometer connected between pins 1 and 8 with the wiper to V^+ . The OP-97 will upgrade circuit designs using 725, OP-05, OP-07 and OP-12 amplifiers.


For applications requiring improved price and/or performance refer to the LT1012 and LT1097 datasheets.

Protected by U.S. patents 4,575,685 and 4,775,884

Instrumentation Amplifier with ± 100 V Common Mode Range





Typical Distribution of Input Bias Current



ABSOLUTE MAXIMUM RATINGS

Supply Voltage	$\pm 20\text{V}$
Differential Input Current (Note 1)	$\pm 10\text{mA}$
Input Voltage	$\pm 20\text{V}$
Output Short Circuit Duration	Indefinite
Operating Temperature Range	
OP-97A	-55°C to 125°C
OP-97E	-40°C to 85°C
Storage Temperature Range	
All Devices	-65°C to 150°C
Lead Temperature (Soldering, 10 sec.)	300°C

PACKAGE/ORDER INFORMATION

 TOP VIEW 8-LEAD TO-5 METAL CAN	ORDER PART NUMBER
	OP-97AH OP-97EH
 TOP VIEW J8 PACKAGE 8-LEAD CERAMIC DIP N8 PACKAGE 8-LEAD PLASTIC DIP	OP-97AJ8 OP-97EJ8 OP-97EN8

ELECTRICAL CHARACTERISTICS $V_S = \pm 15\text{V}$, $V_{CM} = 0\text{V}$, $T_A = 25^{\circ}\text{C}$, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	OP-97A/E			UNITS
			MIN	TYP	MAX	
V_{OS}	Input Offset Voltage			10	25	μV
$\frac{\Delta V_{OS}}{\Delta \text{Time}}$	Long Term Offset Voltage Stability			0.3		$\mu\text{V}/\text{Month}$
I_{OS}	Input Offset Current			30	100	pA
I_B	Input Bias Current			± 30	± 100	pA
e_n	Input Noise Voltage	0.1Hz to 10Hz		0.5		$\mu\text{Vp-p}$
	Input Noise Voltage Density	$f_o = 10\text{Hz}$ (Note 3) $f_o = 1000\text{Hz}$ (Note 4)		17 14	30 22	$\text{nV}/\sqrt{\text{Hz}}$ $\text{nV}/\sqrt{\text{Hz}}$
i_n	Input Noise Current Density	$f_o = 10\text{Hz}$		20		$\text{fA}/\sqrt{\text{Hz}}$
A_{VOL}	Large Signal Voltage Gain	$V_O = \pm 10\text{V}$; $R_L = 2\text{k}\Omega$	300	2000		V/mV
CMRR	Common Mode Rejection Ratio	$V_{CM} = \pm 13.5\text{V}$	114	132		dB
PSRR	Power Supply Rejection Ratio	$V_S = \pm 2\text{V}$ to $\pm 20\text{V}$	114	132		dB
	Input Voltage Range	(Note 2)	± 13.5	± 14.0		V
V_{OUT}	Output Voltage Swing	$R_L = 10\text{k}\Omega$	± 13	± 14		V
SR	Slew Rate		0.1	0.2		$\text{V}/\mu\text{s}$
	Differential Input Resistance	(Note 5)	30			$\text{M}\Omega$
	Closed-Loop Bandwidth	$A_{VCL} = +1$ (Note 5)	0.4	0.9		MHz
I_S	Supply Current			380	600	μA
V_S	Supply Voltage	Operating Range	± 2	± 15	± 20	V

ELECTRICAL CHARACTERISTICS

$V_S = \pm 15V$, $V_{CM} = 0V$, $-40^\circ C \leq T_A \leq 85^\circ C$ for the OP-97E and $-55^\circ C \leq T_A \leq 125^\circ C$ for the OP-97A unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	OP-97A/E			UNITS	
			MIN	TYP	MAX		
V _{OS}	Input Offset Voltage		●	25	60	μV	
TCV _{OS}	Average Temperature Coefficient of V _{OS}		●	0.2	0.6	μV/°C	
I _{OS}	Input Offset Current		●	60	250	pA	
TCI _{OS}	Average Temperature Coefficient of I _{OS}		●	0.4	2.5	pA/°C	
I _B	Input Bias Current	OP-97A	●	± 60	± 600	pA	
		OP-97E	●	± 60	± 250	pA	
TCI _B	Average Temperature Coefficient of I _B	OP-97A	●	0.4	6.0	pA/°C	
		OP-97E	●	0.4	2.5	pA/°C	
A _{VOL}	Large Signal Voltage Gain	V _O = ± 10V; R _L = 2kΩ	●	200	1000	V/mV	
CMRR	Common Mode Rejection Ratio	V _{CM} = ± 13.5V	●	108	128	dB	
PSRR	Power Supply Rejection Ratio	V _S = ± 2.5V to ± 20V	●	108	126	dB	
	Input Voltage Range	(Note 2)	●	± 13.5	± 14.0	V	
V _{OUT}	Output Voltage Swing	R _L = 10kΩ	●	± 13	± 14	V	
SR	Slew Rate	(Note 6)	●	0.05	0.15	V/μS	
I _S	Supply Current		●	400	800	μA	
V _S	Supply Voltage	Operating Range	●	± 2.5	± 15	± 20	V

The ● denotes the specifications which apply over the full operating temperature range.

Note 1: Differential input voltages greater than 1V will cause excessive current to flow through the input protection diodes unless limiting resistance is used.

Note 2: Guaranteed by CMRR test.

Note 3: 10Hz noise voltage density is sample tested. Devices 100% tested for noise are available on request.


Note 4: Sample tested.

Note 5: Guaranteed by design.


Note 6: Guaranteed by design and correlation to $25^\circ C$ limit.

TYPICAL PERFORMANCE CHARACTERISTICS


Typical Distribution of Input Offset Voltage






Typical Distribution of Input Offset Current




Input Bias Current Over Common Mode Range



TYPICAL PERFORMANCE CHARACTERISTICS




Small Signal Transient Response




AV = +1, CLOAD = 100pF, 5μs/DIV

Large Signal Transient Response




AV = +1, 20μs/DIV

Slew Rate, Gain Bandwidth Product vs Over-Compensation Capacitor




Optional Offset Nulling and Over-Compensation Circuits




WITH A 5k TO 100k POTENTIOMETER, INPUT OFFSET VOLTAGE CAN BE ADJUSTED OVER A ±800μV RANGE. THE OVER-COMPENSATION CAPACITOR, CS, CAN BE USED TO IMPROVE CAPACITIVE LOAD HANDLING CAPABILITY, NARROW NOISE BANDWIDTH, OR STABILIZE CIRCUITS WITH GAIN IN THE FEEDBACK LOOP.

Common Mode Rejection vs Frequency



Power Supply Rejection vs Frequency



Please see Linear Technology Databook for package descriptions.