

## 200mA Low-Dropout Linear Regulator with Pin-Selectable Dual-Voltage Level Output

### FEATURES

- **Very Low Dropout:** 230mV Typical at 200mA
- **3% Accuracy Over Load/Line/Temperature**
- **Low  $I_Q$ :** 50 $\mu$ A in Active Mode
- **Available in Fixed-Output Voltages From 0.9V to 3.6V Using Innovative Factory EEPROM Programming**
- **VSET Pin Toggles Output Voltage Between Two Preset Levels**
  - Preset Output Voltage Levels Can Be EEPROM-Programmed To Any Combination
- **High PSRR:** 65dB at 1kHz
- **Stable with a 1.0 $\mu$ F Ceramic Capacitor**
- **Thermal Shutdown and Over-Current Protection**
- **Available in Wafer-Level Chip Scale and 2mm x 2mm SON Packages**

### APPLICATIONS

- **Power Rails with Programming Mode**
- **Dual Voltage Levels for Power-Saving Mode**
- **Leakage Reduction for 90nm and 65nm Processors**
- **Wireless Handsets, Smart Phones, PDAs**
- **MP3 Players and Other Handheld Products**

### DESCRIPTION


The TPS728xx series of low-dropout linear regulators (LDOs), with a selectable dual-voltage level output, is designed specially for applications that require two levels of output voltage regulation. Programming fuses and memory cards, reducing leakage effects, and conserving power in nanometric processes are some application examples.

The VSET pin is used to select one of two output voltage levels preset through innovative factory EEPROM programming. A precision bandgap and error amplifier provides an overall 3% accuracy over load, line, and temperature extremes.


Ultra-small wafer chip scale (WCSP) and 2mm x 2mm SON packages make the TPS728xx series ideal for handheld applications.

This family of devices is fully specified over a temperature range of  $T_J = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

**TPS728xx Series  
YZU PACKAGE  
WCSP-5  
(TOP VIEW)**



**TPS728xx Series  
DRV PACKAGE  
2mm x 2mm SON-6  
(TOP VIEW)**



- (1) It is recommended that the SON package thermal pad be connected to ground.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### ORDERING INFORMATION<sup>(1)</sup>

| PRODUCT          | V <sub>OUT</sub> <sup>(2)</sup>                                                                                                                                                                                                                                                                                         |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TPS728vvvxxxyyyz | <b>VVV</b> is the nominal output voltage for V <sub>OUT1</sub> and corresponds to V <sub>SET</sub> = Low.<br><b>XXX</b> is the nominal output voltage for V <sub>OUT2</sub> and corresponds to V <sub>SET</sub> = High.<br><b>YYY</b> is package designator.<br><b>Z</b> is Tape and reel quantity (R = 3000, T = 250). |

- (1) For the most current package and ordering information see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).
- (2) Output voltages from 0.9V to 3.6V in 50mV increments are available through the use of innovative factory EEPROM programming; minimum order quantities may apply. Contact factory for details and availability.

### ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

At T<sub>J</sub> = –40°C to +125°C (unless otherwise noted). All voltages are with respect to GND.

| PARAMETER                                                           |                            | TPS728xx Series                               | UNIT |
|---------------------------------------------------------------------|----------------------------|-----------------------------------------------|------|
| Input voltage range, V <sub>IN</sub>                                |                            | –0.3 to +7.0                                  | V    |
| Enable and VSET voltage range, V <sub>EN</sub> and V <sub>SET</sub> |                            | –0.3 to V <sub>IN</sub> + 0.3 <sup>(2)</sup>  | V    |
| Output voltage range, V <sub>OUT</sub>                              |                            | –0.3 to +7.0                                  | V    |
| Maximum output current, I <sub>OUT</sub>                            |                            | Internally limited                            |      |
| Output short-circuit duration                                       |                            | Indefinite                                    |      |
| Total continuous power dissipation, P <sub>DISS</sub>               |                            | See <a href="#">Dissipation Ratings</a> Table |      |
| ESD rating                                                          | Human body model (HBM)     | 2                                             | kV   |
|                                                                     | Charged device model (CDM) | 500                                           | V    |
| Operating junction temperature range, T <sub>J</sub>                |                            | –55 to +150                                   | °C   |
| Storage temperature range, T <sub>STG</sub>                         |                            | –55 to +150                                   | °C   |

- (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.
- (2) V<sub>EN</sub> and V<sub>SET</sub> absolute maximum rating is V<sub>IN</sub> + 0.3V or +7.0V, whichever is less.

### DISSIPATION RATINGS

| BOARD                 | PACKAGE | R <sub>θJC</sub> | R <sub>θJA</sub> | DERATING FACTOR<br>ABOVE T <sub>A</sub> = +25°C | T <sub>A</sub> < +25°C | T <sub>A</sub> = +70°C | T <sub>A</sub> = +85°C |
|-----------------------|---------|------------------|------------------|-------------------------------------------------|------------------------|------------------------|------------------------|
| High-K <sup>(1)</sup> | DRV     | 20°C/W           | 65°C/W           | 15.4mW/°C                                       | 1540mW                 | 845mW                  | 615mW                  |
| High-K <sup>(1)</sup> | YZU     | 85°C/W           | 268°C/W          | 3.7mW/°C                                        | 370mW                  | 205mW                  | 150mW                  |


- (1) The JEDEC high-K (2s2p) board used to derive this data was a 3- × 3-inch, multilayer board with 1-ounce internal power and ground planes and 2-ounce copper traces on top and bottom of the board.

## ELECTRICAL CHARACTERISTICS


Over operating temperature range ( $T_J = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  
 $I_{OUT} = 0.5\text{mA}$ ,  $V_{SET} = V_{EN} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^{\circ}\text{C}$ .

| PARAMETER                     |                                                                                                                       |                                         | TEST CONDITIONS                                                                                                                     | MIN                 | TYP                 | MAX      | UNIT                       |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------------------|----------|----------------------------|
| $V_{IN}$                      | Input voltage range                                                                                                   |                                         |                                                                                                                                     | 2.7                 |                     | 6.5      | V                          |
| $V_{OUT}^{(1)}$               | DC output accuracy                                                                                                    | Nominal                                 | $T_J = +25^{\circ}\text{C}$ , $V_{SET} = \text{high/low}$                                                                           | -2.5                |                     | +2.5     | mV                         |
|                               |                                                                                                                       | Over $V_{IN}$ , $I_{OUT}$ , temperature | $V_{OUT} + 0.5\text{V} \leq V_{IN} \leq 6.5\text{V}$ ,<br>$0\text{mA} \leq I_{OUT} \leq 200\text{mA}$ , $V_{SET} = \text{high/low}$ | -3.0                |                     | +3.0     | %                          |
| $\Delta V_{OUT}$              | Load transient                                                                                                        |                                         | 100 $\mu\text{A}$ to 200mA in 1 $\mu\text{s}$ ,<br>200mA to 100 $\mu\text{A}$ in 1 $\mu\text{s}$ , $C_{OUT} = 1\mu\text{F}$         |                     | $\pm 60.0$          |          | mV                         |
| $V_O$                         | Output voltage range                                                                                                  |                                         |                                                                                                                                     | 0.9                 |                     | 3.6      | V                          |
| $\Delta V_O / \Delta V_{IN}$  | Line regulation                                                                                                       |                                         | $V_{OUT(NOM)} + 0.5\text{V} \leq V_{IN} \leq 6.5\text{V}$ ,<br>$I_{OUT} = 5\text{mA}$                                               |                     | 130                 |          | $\mu\text{V/V}$            |
| $\Delta V_O / \Delta I_{OUT}$ | Load regulation                                                                                                       |                                         | $0\text{mA} \leq I_{OUT} \leq 200\text{mA}$                                                                                         |                     | 75                  |          | $\mu\text{V/mA}$           |
| $V_{DO}$                      | Dropout voltage <sup>(2)</sup>                                                                                        |                                         | $V_{IN} = V_{OUT(NOM)} - 0.1\text{V}$ , $I_{OUT} = 200\text{mA}$                                                                    |                     | 230                 | 400      | mV                         |
| $I_{CL}$                      | Output current limit                                                                                                  |                                         | $V_{OUT} = 0.9 \times V_{OUT(NOM)}$                                                                                                 | 240                 | 340                 | 575      | mA                         |
| $I_{GND}$                     | Ground pin current                                                                                                    |                                         | $I_{OUT} = 0\text{mA}$                                                                                                              |                     | 50                  | 80       | $\mu\text{A}$              |
|                               |                                                                                                                       |                                         | $I_{OUT} = 200\text{mA}$                                                                                                            |                     | 120                 |          | $\mu\text{A}$              |
| $I_{SHDN}$                    | Shutdown current ( $I_{GND}$ )                                                                                        |                                         | $V_{EN} \leq 0.4\text{V}$ , $2.7\text{V} \leq V_{IN} < 4.5\text{V}$ ,<br>$T_J = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$       |                     | 0.10                | 1.0      | $\mu\text{A}$              |
| PSRR                          | Power-supply rejection ratio                                                                                          |                                         | $V_{IN} = 3.8\text{V}$ ,<br>$V_{OUT} = 2.8\text{V}$ ,<br>$I_{OUT} = 200\text{mA}$                                                   | $f = 100\text{Hz}$  | 65                  |          | dB                         |
|                               |                                                                                                                       |                                         |                                                                                                                                     | $f = 1\text{kHz}$   | 65                  |          | dB                         |
|                               |                                                                                                                       |                                         |                                                                                                                                     | $f = 10\text{kHz}$  | 55                  |          | dB                         |
|                               |                                                                                                                       |                                         |                                                                                                                                     | $f = 100\text{kHz}$ | 40                  |          | dB                         |
| $V_N$                         | Output noise voltage                                                                                                  |                                         | $\text{BW} = 100\text{Hz}$ to $100\text{kHz}$ , $V_{IN} = 3.3\text{V}$ ,<br>$V_{OUT} = 2.8\text{V}$ , $I_{OUT} = 10\text{mA}$       |                     | $75 \times V_{OUT}$ |          | $\mu\text{V}_{\text{RMS}}$ |
| $t_{TR}$                      | Transition time (low-to-high)<br>$V_{OUT} = V_{OUT\_LOW}$ to $V_{OUT\_HIGH}$<br>$V_{OUT} = 97\% \times V_{OUT\_HIGH}$ |                                         | $V_{OUT\_LOW} = 1.8\text{V}$ , $V_{OUT\_HIGH} = 3.15\text{V}$ ,<br>$I_{OUT} = 10\text{mA}$                                          |                     | 60                  |          | $\mu\text{s}$              |
| $t_{STR}$                     | Startup time <sup>(3)</sup>                                                                                           |                                         | $C_{OUT} = 1.0\mu\text{F}$                                                                                                          |                     | 160                 |          | $\mu\text{s}$              |
| $t_{SHUT}$                    | Shutdown time <sup>(4)</sup>                                                                                          |                                         | $R_L = \infty$ , $C_{OUT} = 1.0\mu\text{F}$ , $V_{OUT} = 2.8\text{V}$                                                               |                     | 180 <sup>(5)</sup>  |          | $\mu\text{s}$              |
| $V_{HI}$                      | VSET high (output $V_{OUT2}$ selected),<br>or enable pin high (enabled)                                               |                                         |                                                                                                                                     | 1.2                 |                     | $V_{IN}$ | V                          |
| $V_{LO}$                      | VSET low (output $V_{OUT1}$ selected),<br>or enable pin low (disabled)                                                |                                         |                                                                                                                                     | 0                   |                     | 0.4      | V                          |
| $I_{EN}$ , $I_{VSET}$         | Enable and select pin currents                                                                                        |                                         | $EN = VSET = 6.5\text{V}$                                                                                                           |                     | 0.04                | 1.0      | $\mu\text{A}$              |
| UVLO                          | Undervoltage lockout                                                                                                  |                                         | $V_{IN}$ rising, $V_{SET} = \text{high/low}$                                                                                        | 2.38                | 2.51                | 2.65     | V                          |
|                               | Hysteresis                                                                                                            |                                         | $V_{IN}$ falling, $V_{SET} = \text{high/low}$                                                                                       |                     | 230                 |          | mV                         |
| $T_{SD}$                      | Thermal shutdown temperature                                                                                          |                                         | Shutdown, temperature increasing                                                                                                    |                     | +160                |          | $^{\circ}\text{C}$         |
|                               |                                                                                                                       |                                         | Reset, temperature decreasing                                                                                                       |                     | +140                |          | $^{\circ}\text{C}$         |
| $T_J$                         | Operating junction temperature                                                                                        |                                         |                                                                                                                                     | -40                 |                     | +125     | $^{\circ}\text{C}$         |


- (1) The output voltage for  $V_{SET} = \text{low/high}$  is programmed at the factory.
- (2)  $V_{DO}$  is not measured for devices with  $V_{OUT(NOM)} < 2.8\text{V}$  because minimum  $V_{IN} = 2.7\text{V}$ .
- (3) Time from  $V_{EN} = 1.2\text{V}$  to  $V_{OUT} = 97\%$  ( $V_{OUT(NOM)}$ ).
- (4) Time from  $V_{EN} = 0.4\text{V}$  to  $V_{OUT} = 5\%$  ( $V_{OUT(NOM)}$ ).
- (5) See [Shutdown](#) in the *Application Information* section for more details.

**DEVICE INFORMATION****Figure 1. Functional Block Diagram**

**YZU PACKAGE  
WCSP-5  
(TOP VIEW)**



**DRV PACKAGE  
SON-8  
(TOP VIEW)**



- (1) It is recommended that the SON package thermal pad be connected to ground.

**PIN DESCRIPTIONS**

| TPS728xx Series |     |     | DESCRIPTION                                                                                                                                                                                                                                    |
|-----------------|-----|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME            | DRV | YZU |                                                                                                                                                                                                                                                |
| OUT             | 1   | C1  | Regulated output voltage pin. A small 1μF ceramic capacitor is needed from this pin to ground to assure stability. See <a href="#">Input and Output Capacitor Requirements</a> in the <i>Application Information</i> section for more details. |
| VSET            | 2   | A3  | Select pin. Driving VSET below 0.4V selects preset output voltage $V_{OUT1}$ . Driving VSET over 1.2V selects preset output voltage $V_{OUT2}$ .                                                                                               |
| NC              | 3   | —   | No connection.                                                                                                                                                                                                                                 |
| EN              | 4   | A1  | Enable pin. Driving EN over 1.2V turns on the regulator. Driving EN below 0.4V puts the regulator into shutdown mode, thus reducing the operating current to 100nA, nominal.                                                                   |
| GND             | 5   | B2  | Ground pin (connect DRV thermal pad to ground)                                                                                                                                                                                                 |
| IN              | 6   | C3  | Input pin. A small capacitor is needed from this pin to ground to assure stability. See <a href="#">Input and Output Capacitor Requirements</a> in the <i>Application Information</i> section for more details.                                |

## TYPICAL CHARACTERISTICS

Over operating temperature range ( $T_J = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  
 $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ .




Figure 2.




Figure 3.




Figure 4.




Figure 5.




Figure 6.




Figure 7.

## TYPICAL CHARACTERISTICS (continued)

Over operating temperature range ( $T_J = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  
 $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ .




Figure 8.




Figure 9.




Figure 10.




Figure 11.




Figure 12.




Figure 13.

### TYPICAL CHARACTERISTICS (continued)

Over operating temperature range ( $T_J = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  
 $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ .




Figure 14.




Figure 15.




Figure 16.




Figure 17.




Figure 18.




Figure 19.

## TYPICAL CHARACTERISTICS (continued)

Over operating temperature range ( $T_J = -40^\circ\text{C}$  to  $+125^\circ\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  
 $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ .




Figure 20.




Figure 21.




Figure 22.




Figure 23.




Figure 24.




Figure 25.

### TYPICAL CHARACTERISTICS (continued)

Over operating temperature range ( $T_J = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^{\circ}\text{C}$ .




Figure 26.




Figure 27.




Figure 28.




Figure 29.




Figure 30.




Figure 31.

## TYPICAL CHARACTERISTICS (continued)

Over operating temperature range ( $T_J = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^{\circ}\text{C}$ .




Figure 32.




Figure 33.




Figure 34.




Figure 35.




Figure 36.





Figure 37.

**TYPICAL CHARACTERISTICS (continued)**

Over operating temperature range ( $T_J = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ ),  $V_{IN} = V_{OUT(TYP)} + 0.5\text{V}$  or  $2.7\text{V}$ , whichever is greater;  $I_{OUT} = 0.5\text{mA}$ ,  $V_{EN} = V_{SET} = V_{IN}$ ,  $C_{OUT} = 1.0\mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^{\circ}\text{C}$ .

**Figure 38.**

## APPLICATION INFORMATION

The TPS728xx series belongs to a family of new generation LDO regulators that use innovative circuitry to achieve ultra-wide bandwidth and high loop gain, resulting in extremely high PSRR (up to 1MHz) at very low headroom ( $V_{IN} - V_{OUT}$ ). These features, combined with low noise, low ground pin current, and ultra-small packaging, make this device ideal for portable applications. This family of regulators offers sub-bandgap output voltages, current limit and thermal protection, and is fully specified from  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ .

Figure 39 shows the basic circuit connections.




Figure 39. Typical Application Circuit

## APPLICATION EXAMPLES

EEPROM-based applications require the programming voltage to be higher than the operating voltage. The TPS728xx suits such applications where the maximum programming voltage of the EEPROM is higher than the operating voltage. The VSET logic pin allows the application to transition between the higher EEPROM programming voltage and the lower operating voltage. For example, the TPS728xx typically takes less than  $40\mu\text{s}$  to transition from a lower voltage of 1.85V to a higher voltage of 3.15V under an output load of 1mA to 10mA, as shown in Figure 35 and Figure 37, respectively. The special circuitry in the TPS728xx helps transition from the higher voltage to the lower voltage under no load. The load on the output at the end of the programming cycle is typically under 10mA. Output voltage overshoots and undershoots are minimal under this load condition. The TPS728xx typically takes less than 1ms of transition time going from 3.15V to 1.85V, as shown in Figure 36 and Figure 38, respectively. Both output states of the TPS728xx are programmable between 0.9V to 3.6V.

Another area where the TPS728xx can be used effectively is in dynamic voltage scaling (DVS) applications. In DVS applications, it is required to dynamically switch between a high operational voltage to a low standby voltage in order to balance performance of processors and achieve power savings. Modern multimillion gate microprocessors fabricated with the latest sub-micron processes save on power by transitioning to a lower voltage to reduce leakage currents without losing content. This architecture enables the microprocessor to transition quickly into an operational state (wake up) without requiring reloading of the states from external memory, or a reboot.

## INPUT AND OUTPUT CAPACITOR REQUIREMENTS

Although an input capacitor is not required for stability, it is good analog design practice to connect a  $0.1\mu\text{F}$  to  $1.0\mu\text{F}$  low equivalent series resistance (ESR) capacitor across the input supply near the regulator. This capacitor counteracts reactive input sources and improves transient response, noise rejection, and ripple rejection. A higher-value capacitor may be necessary if large, fast rise-time load transients are anticipated, or if the device is not located near the power source. If source impedance is not sufficiently low, a  $0.1\mu\text{F}$  input capacitor may be necessary to ensure stability.

The TPS728xx is designed to be stable with standard ceramic capacitors with values of  $1.0\mu\text{F}$  or larger at the output. X5R- and X7R-type capacitors are best because they have minimal variation in value and ESR over temperature. Maximum ESR should be less than  $1.0\Omega$ .

## BOARD LAYOUT RECOMMENDATIONS TO IMPROVE PSRR AND NOISE PERFORMANCE

To improve ac performance such as PSRR, output noise, and transient response, it is recommended that the board be designed with separate ground planes for  $V_{IN}$  and  $V_{OUT}$ , with each ground plane connected only at the GND pin of the device. In addition, the ground connection for the output capacitor should connect directly to the GND pin of the device. High ESR capacitors may degrade PSRR.

## INTERNAL CURRENT LIMIT

The TPS728xx internal current limits help protect the regulator during fault conditions. During current limit, the output sources a fixed amount of current that is largely independent of output voltage. For reliable operation, the device should not be operated in a current limit state for extended periods of time.

The PMOS pass element in the TPS728xx has a built-in body diode that conducts current when the voltage at OUT exceeds the voltage at IN. This current is not limited, so if extended reverse voltage operation is anticipated, external limiting to 5% of rated output current may be appropriate.

## SHUTDOWN

The enable pin (EN) is active high and is compatible with standard and low voltage, TTL-CMOS levels. When shutdown capability is not required, EN can be connected to the IN pin, as shown in Figure 40. Figure 41 shows when both EN and VSET are tied to IN. The TPS728xx, with internal active output pulldown circuitry, discharges the output to within 5% of  $V_{OUT}$  with a time ( $t$ ) of:

$$t = 3 \left[ \frac{60 \times R_L}{60 + R_L} \right] \times C_{OUT}$$

Where:

$R_L$  = output load resistance

$C_{OUT}$  = output capacitance

## DROPOUT VOLTAGE

The TPS728xx uses a PMOS pass transistor to achieve low dropout. When  $(V_{IN} - V_{OUT})$  is less than the dropout voltage ( $V_{DO}$ ), the PMOS pass device is in the linear region of operation and the input-to-output resistance is the  $R_{DS(ON)}$  of the PMOS pass element.  $V_{DO}$  approximately scales with output current because the PMOS device behaves like a resistor in dropout.

As with any linear regulator, PSRR and transient response are degraded as  $(V_{IN} - V_{OUT})$  approaches dropout. This effect is shown in Figure 25 and Figure 26 in the Typical Characteristics section.

## TRANSIENT RESPONSE

As with any regulator, increasing the size of the output capacitor reduces over/undershoot magnitude but increases duration of the transient response.




Figure 40. Circuit Showing EN Tied High when Shutdown Capability is Not Required




Figure 41. Circuit to Tie Both EN and VSET High

## UNDERVOLTAGE LOCK-OUT (UVLO)

The TPS728xx uses an undervoltage lock-out circuit to keep the output shut off until the internal circuitry is operating properly. The UVLO circuit has a deglitch feature so that it typically ignores undershoot transients on the input if they are less than 5μs duration. The UVLO circuit triggers at approximately 2.3V on an undershooting or a falling input voltage. On the TPS728xx, the active pulldown discharges  $V_{OUT}$  when the device is in UVLO off condition. However, the input voltage must be greater than 0.8V for the active pulldown to work.

## MINIMUM LOAD

The TPS728xx is stable with no output load. Traditional PMOS LDO regulators suffer from lower loop gain at very light output loads. The TPS728xx employs an innovative, low-current mode circuit under very light or no-load conditions, resulting in improved output voltage regulation performance down to zero output current.

## THERMAL INFORMATION

### Thermal Protection

Thermal protection disables the output when the junction temperature rises to approximately +160°C, allowing the device to cool. When the junction temperature cools to approximately +140°C the output circuitry is again enabled. Depending on power dissipation, thermal resistance, and ambient temperature, the thermal protection circuit may cycle on and off. This cycling limits the dissipation of the regulator, protecting it from damage as a result of overheating.

Any tendency to activate the thermal protection circuit indicates excessive power dissipation or an inadequate heatsink. For reliable operation, junction temperature should be limited to +125°C maximum. To estimate the margin of safety in a complete design (including heatsink), increase the ambient temperature until the thermal protection is triggered; use worst-case loads and signal conditions. For good reliability, thermal protection should trigger at least +35°C above the maximum expected ambient condition of your particular application. This configuration produces a worst-case junction temperature of +125°C at the highest expected ambient temperature and worst-case load.

The internal protection circuitry of the TPS728xx has been designed to protect against overload conditions.

It was not intended to replace proper heatsinking. Continuously running the TPS728xx into thermal shutdown degrades device reliability.

### Power Dissipation


The ability to remove heat from the die is different for each package type, presenting different considerations in the printed circuit board (PCB) layout. The PCB area around the device that is free of other components moves the heat from the device to the ambient air. Performance data for JEDEC low- and high-K boards are given in the [Dissipation Ratings](#) table. Using heavier copper increases the effectiveness in removing heat from the device. The addition of plated through-holes to heat-dissipating layers also improves the heatsink effectiveness.

Power dissipation depends on input voltage and load conditions. Power dissipation ( $P_D$ ) is equal to the product of the output current times the voltage drop across the output pass element ( $V_{IN}$  to  $V_{OUT}$ ), as shown in [Equation 1](#):

$$P_D = (V_{IN} - V_{OUT}) \times I_{OUT} \quad (1)$$

### Package Mounting

Solder pad footprint recommendations for the TPS728xx are available from the Texas Instruments web site at [www.ti.com](http://www.ti.com).



**Figure 42. YZU Wafer Chip-Scale Package Dimensions (in mm)**

**PACKAGING INFORMATION**

| Orderable Device   | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|--------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| TPS728120150DRVR   | ACTIVE        | SON          | DRV                | 6    | 3000           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | DAO                     | <a href="#">Samples</a> |
| TPS728120150DRV    | ACTIVE        | SON          | DRV                | 6    | 250            | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | DAO                     | <a href="#">Samples</a> |
| TPS728175295YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | AU                      | <a href="#">Samples</a> |
| TPS728175295YZUT   | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | AU                      | <a href="#">Samples</a> |
| TPS728180285YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | DT                      | <a href="#">Samples</a> |
| TPS728180285YZUT   | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | DT                      | <a href="#">Samples</a> |
| TPS728180300YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | VL                      | <a href="#">Samples</a> |
| TPS728180300YZUT   | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | VL                      | <a href="#">Samples</a> |
| TPS728185295YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | VM                      | <a href="#">Samples</a> |
| TPS728185295YZUT   | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | VM                      | <a href="#">Samples</a> |
| TPS728185315DRVR   | ACTIVE        | SON          | DRV                | 6    | 3000           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | BYW                     | <a href="#">Samples</a> |
| TPS728185315DRVRG4 | ACTIVE        | SON          | DRV                | 6    | 3000           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | BYW                     | <a href="#">Samples</a> |
| TPS728185315DRV    | ACTIVE        | SON          | DRV                | 6    | 250            | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | BYW                     | <a href="#">Samples</a> |
| TPS728185315YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | FN                      | <a href="#">Samples</a> |
| TPS728185315YZUT   | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | FN                      | <a href="#">Samples</a> |
| TPS728285180DRVR   | PREVIEW       | SON          | DRV                | 6    |                | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         |                         |
| TPS728285180DRV    | PREVIEW       | SON          | DRV                | 6    |                | TBD                        | Call TI                 | Call TI              | -40 to 125   |                         |                         |
| TPS728285180YZUR   | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | TL                      | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| TPS728285180YZUT | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | TL                      | <a href="#">Samples</a> |
| TPS728330180YZUR | ACTIVE        | DSBGA        | YZU                | 5    | 3000           | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | DJ                      | <a href="#">Samples</a> |
| TPS728330180YZUT | ACTIVE        | DSBGA        | YZU                | 5    | 250            | Green (RoHS<br>& no Sb/Br) | SNAGCU                  | Level-1-260C-UNLIM   | -40 to 125   | DJ                      | <a href="#">Samples</a> |
| TPS728330185DRVR | ACTIVE        | SON          | DRV                | 6    | 3000           | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | SBD                     | <a href="#">Samples</a> |
| TPS728330185DRVT | ACTIVE        | SON          | DRV                | 6    | 250            | Green (RoHS<br>& no Sb/Br) | CU NIPDAU               | Level-1-260C-UNLIM   | -40 to 125   | SBD                     | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TPS728120150DRV  | SON          | DRV             | 6    | 3000 | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |
| TPS728120150DRV  | SON          | DRV             | 6    | 250  | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |
| TPS728175295YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728175295YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728180285YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728180285YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728180300YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728180300YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728185295YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728185295YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728185315DRV  | SON          | DRV             | 6    | 3000 | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |
| TPS728185315DRV  | SON          | DRV             | 6    | 250  | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |
| TPS728185315YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728185315YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728285180YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728285180YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728330180YZUR | DSBGA        | YZU             | 5    | 3000 | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |
| TPS728330180YZUT | DSBGA        | YZU             | 5    | 250  | 180.0              | 8.4                | 1.07    | 1.42    | 0.74    | 4.0     | 8.0    | Q1            |

| Device           | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TPS728330185DRVR | SON          | DRV             | 6    | 3000 | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |
| TPS728330185DRVT | SON          | DRV             | 6    | 250  | 179.0              | 8.4                | 2.2     | 2.2     | 1.2     | 4.0     | 8.0    | Q2            |

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal


| Device           | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TPS728120150DRVR | SON          | DRV             | 6    | 3000 | 203.0       | 203.0      | 35.0        |
| TPS728120150DRVT | SON          | DRV             | 6    | 250  | 203.0       | 203.0      | 35.0        |
| TPS728175295YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728175295YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728180285YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728180285YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728180300YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728180300YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728185295YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728185295YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728185315DRVR | SON          | DRV             | 6    | 3000 | 203.0       | 203.0      | 35.0        |
| TPS728185315DRVT | SON          | DRV             | 6    | 250  | 203.0       | 203.0      | 35.0        |
| TPS728185315YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728185315YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728285180YZUR | DSBGA        | YZU             | 5    | 3000 | 210.0       | 185.0      | 35.0        |

---

| Device           | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TPS728285180YZUT | DSBGA        | YZU             | 5    | 250  | 210.0       | 185.0      | 35.0        |
| TPS728330180YZUR | DSBGA        | YZU             | 5    | 3000 | 182.0       | 182.0      | 17.0        |
| TPS728330180YZUT | DSBGA        | YZU             | 5    | 250  | 182.0       | 182.0      | 17.0        |
| TPS728330185DRVR | SON          | DRV             | 6    | 3000 | 203.0       | 203.0      | 35.0        |
| TPS728330185DRVT | SON          | DRV             | 6    | 250  | 203.0       | 203.0      | 35.0        |

DRV (S-PWSON-N6)

PLASTIC SMALL OUTLINE NO-LEAD



4206925/E 10/10

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Small Outline No-Lead (SON) package configuration.
  -  D. The package thermal pad must be soldered to the board for thermal and mechanical performance. See the Product Data Sheet for details regarding the exposed thermal pad dimensions.

## THERMAL PAD MECHANICAL DATA

DRV (S-PWSON-N6)


PLASTIC SMALL OUTLINE NO-LEAD

### THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at [www.ti.com](http://www.ti.com).

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View


Exposed Thermal Pad Dimensions

4206926/0 01/14

NOTE: All linear dimensions are in millimeters

DRV (S-PWSON-N6)


PLASTIC SMALL OUTLINE NO-LEAD



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at [www.ti.com](http://www.ti.com) <<http://www.ti.com>>.
  - E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
  - F. Customers should contact their board fabrication site for solder mask tolerances.

YZU (R-XBGA-N5)

DIE-SIZE BALL GRID ARRAY



D: Max = 1.358 mm, Min = 1.297 mm

E: Max = 0.99 mm, Min = 0.93 mm

4205678/E 07/13

- Notes:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. NanoFree™ package configuration.

NanoFree is a trademark of Texas Instruments.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

### Products

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Audio                        | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers                   | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters              | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products                | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                          | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers            | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface                    | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                        | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt                   | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers             | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                         | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Applications Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity        | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

### TI E2E Community

[e2e.ti.com](http://e2e.ti.com)