
PCN Number:			201	20160908002					PCN Date: Sept 19, 2016					
Title: Assembly and			and Tes	d Test site move from MLA to PTIAT for Select Devices										
Customer Contact: P			: PCN	PCN Manager				Quali	Quality Services					
Proposed 1 st Ship Da			Date:					Estimated Sample Availability:			Date provided at sample request			
Cha	ange	Туре:						-		•				
	Asse	embly Site				Desi	ign				Wa	fer Bump Site		
		embly Proce			Data Sheet							fer Bump Mate		
		embly Mate			Part number change					Щ	Wafer Bump Process			
		hanical Spe			☐ Test Site					Wafer Fab Site Wafer Fab Materials				
	Pack	ing/Shippi	ng/Labe	ling	Test Process									
						P	CN Deta	nils			vva	fer Fab Process	>	
Des	scrint	ion of Cha	ange											
Description of Change: Texas Instruments Incorporated is announcing the Assembly and Test site move from MLA to PTIAT for Select Devices listed in the "Product Affected" Section. No Material differences between Sites.														
		bly Site	Assen	Assembly Site Origin				bly Count	ry Cod	le	Assembly Site City			
		alaysia		MLA				MY			Kuala Lumpur			
Т		ertech logy Inc.		PT2			TW				Hsinchu City			
test	Test coverage, insertions, conditions will remain consistent with current testing and verified via test MQ.								fied via					
Rea	ason	for Chang	e:											
Cor	Continuity of supply.													
Ant	ticipa	ted impac	t on Fit	, Form	, Fι	ınctic	n, Quali	ty or Re	liabilit	ty (posi	itive / negativ	/e):	
Nor	ne													
Ant	ticipa	ted impac	t on Ma	terial	Dec	larat	ion							
No Impact to the Material Declaration			pro rel	Material Declarations or Product Content reports are driven from production data and will be available following the production release. Upon production release the revised reports can be obtained from the <u>TI ECO website</u> .										
Changes to product identification resulting from this PCN:														
Sample product shipping label (not actual product label) Assembly Site:														
TI Malaysia				Assembly Site Origin (22L				ASO: MLA						
Powertech Technology Inc.				As	Assembly Site Origin (22L)				ASO: PT2					
Sample product shipping label to show code location (not actual product label)														



ASSEMBLY SITE CODES: MLA=K, PT2 =C

Products Affected

LMZ31704RVQR	LMZ31707RVQR	LMZ31710RVQR	TPS84A20RVQR
LMZ31704RVQT	LMZ31707RVQT	LMZ31710RVQT	TPS84A20RVQT



Qualification Report

LMZ31704RVQ, LMZ31707RVQ, LMZ31710RVQ Approve Date 22-Aug-2016

Product Attributes

Attributes	Qual Device: LMZ31710RVQ	QBS Product Family: LMZ31704RVQ	QBS Product Family: LMZ31707RVQ	QBS Product Reference: LMZ31710RVQ	QBS Package Reference: LMZ36002RVQ
Die Attributes	-	-	-		
Wafer Fab Supplier	TI – Germany	TI - Germany	TI - Germany	TI - Germany	DMOS5
Wafer Process	LBC7	LBC7	LBC7	LBC7	LBC8
Assembly Site	PTI-Taiwan	PTI-Taiwan	PTI-Taiwan	TI - Malaysia	PTI-Taiwan
Package Family	QFN	QFN	QFN	QFN	QFN
Flammability Rating	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0	UL 94 V-0

⁻ QBS: Qual By Similarity

⁻ Qual Device LMZ31704RVQ, LMZ31707RVQ, LMZ31710RVQ are qualified at LEVEL3-260C

Qualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Туре	Test Name / Condition	Duration	Qual Device: LMZ31710RVQ	QBS Product Reference: LMZ31710RVQ	QBS Package Reference: LMZ36002RVQ
PC	Preconditioning Level 3	260C	1/231/0	-	3/231/0
HTOL	Life Test, 125C	1000 hours	1/77/0	2/154/0	-
PTCL	Power Temperature Cycle, 25C/70C	1000 hours	1/40/0	-	-
HTSL	High Temp Storage Bake 150C	1000 hours	1/77/0	-	1/77/0
TC	Temperature Cycle, -65/150C	500 cycles	1/77/0	-	-
TC	Temperature Cycle, -55/125C	700 cycles	-	-	3/231/0
THB	Biased Temperature and Humidity, 85C/85%RH	1000 hours	1/77/0	-	1/77/0
UHAST	Unbiased HAST 110C/85%RH	264 hours	1/77/0	-	3/231/0
HBM	ESD HBM	1500V	-	0/3	-
CDM	ESD CDM	750V	-	0/3	-
ED	Electrical Characterization	-	Pass	Pass	Pass

- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: http://www.ti.com/

Green/Pb-free Status:

Qualified Pb-Free (SMT) and Green

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com